




## 87DPBL-B

### Sheer Bright Chrome 1 gang 20AX Double Pole Rocker Black/Black

| Item Image   | Wiring   | Dimensions   |
|--|--|--|
|   |                                     |   |
| Primary Range  | Sheer  |  |
| Insert Type  | 1 gang 20AX Double Pole Rocker   |  |
| Plate Finish   | Sheer Box Bright Chrome  |  |
| Insert Colour  | Black/Black  |  |
| EAN13 Barcode  | 5017503091973  |  |
| Dimensions (Nominal)   | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm   |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = N/A  |  |
| Minimum Wall Box Depth   | 35mm   |  |
| Switched Poles   | Double   |  |
| Current Rating   | 20AX   |  |
| Voltage  | 220/250V AC  |  |
| Maximum Load   | 20 Amp inductive   |  |
| Mains Frequency  | 50Hz   |  |
| IP Rating  | IP2XD  |  |
| Contact Gap Minimum  | 3mm  |  |
| Terminal Capacity 1  | 3 x 2.5mm <sup>2</sup>   |  |
| Terminal Capacity 2  | 2 x 4mm <sup>2</sup> Multi Strand  |  |
| Terminal Capacity 3  | 1 x 6mm <sup>2</sup>   |  |
| Earth Terminal Capacity 1  | 6 x 1mm <sup>2</sup>   |  |
| Earth Terminal Capacity 2  | 5 x 1.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 4  | 2 x 4mm <sup>2</sup> Multi-strand  |  |
| Earth Terminal Capacity 5  | 1 x 6mm <sup>2</sup>   |  |
| Product Class 1  | Must be earthed  |  |
| Ambient Operating Temperature  | -5° to +40°C   |  |
| Recommended Location   | Internal Use Only  |  |
| Maximum Installation Altitude  | 2000m  |  |
| Standard/Approval  | BS EN 60669-1  |  |
| Patents and Trademarks   | Sheer is a Registered Trade Mark No. 2296586   |  |
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>         | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>                | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p> | <p>Correct as at 17 October 2018 10:01 AM E&amp;OE</p>   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84



Listed in **LUCKINS**



CERT. No. FM12238