

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

87R22BC-B

Sheer Bright Chrome 2 gang 10AX 2 Way Rocker Bright Chrome/Black

Item Image Wiring **Dimensions** Hamilton Primary Range Sheer Insert Type 2 gang 10AX 2 Way Rocker Plate Finish Sheer Box Bright Chrome Insert Colour Bright Chrome/Black EAN13 Barcode 5017503096220 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Weight 138 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX 220/250V AC Voltage Maximum Load 10 Amp inductive 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

All products listed conform to current British or European standard and the product information is

process and are not binding.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

of certain finishes

Sheer is a Registered Trade Mark No. 2296586

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 10:01 AM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Ambient Operating Temperature

Maximum Installation Altitude

Recommended Location

Patents and Trademarks

Standard/Approval

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

-5° to +40°C

2000m

Internal Use Only

BS EN 60669-1















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio