SL

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

87R22BL-B

Sheer Bright Chrome 2 gang 10AX 2 Way Rocker Black/Black

Item Image





Dimensions



| Primary Range | Sheer | |
|---|---|--|
| Insert Type | 2 gang 10AX 2 Way Rocker | |
| Plate Finish | Sheer Box Bright Chrome | |
| Insert Colour | Black/Black | |
| EAN13 Barcode | 5017503091225 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 25mm | |
| Switched Poles | Single | |
| Current Rating | 10AX | |
| Voltage | 220/250V AC | |
| Maximum Load | 10 Amp inductive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 1 x 2.5mm2 | |
| Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Patents and Trademarks | Sheer is a Registered Trade Mark No. 2296586 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









Correct as at 17 October 2018 10:01 AM



Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.