SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

87T22

Sheer Bright Chrome 2 gang 20AX 2 Way Toggle Bright Chrome

Item Image Wiring **Dimensions** Hamilton[®] Primary Range Sheer Insert Type 2 gang 20AX 2 Way Toggle Plate Finish Sheer Box Bright Chrome Insert Colour **Bright Chrome** EAN13 Barcode 5028690092865 Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Single **Current Rating** 20AX 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand

All products listed conform to current British or European standard and the product information is correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

of certain finishes.

Sheer is a Registered Trade Mark No. 2296586

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 10:02 AM

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Earth Terminal Capacity 5

Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Standard/Approval

Ambient Operating Temperature

Product Class 1

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

1 x 6mm2

Must be earthed

BS EN 60669-1

-5° to +40°C Internal Use Only

2000m









