




## 88C2J12B

### Sheer CFX Black Nickel 2 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions																																				
	 <table border="1" data-bbox="808 646 967 730"> <thead> <tr> <th>Pin</th> <th>Color</th> <th>Wire Color</th> <th>Other Colors</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>GREEN / White</td> <td>BLUE</td> <td></td> </tr> <tr> <td>2</td> <td>ORANGE / White</td> <td>YELLOW</td> <td></td> </tr> <tr> <td>3</td> <td>WHITE / Blue</td> <td>GREEN</td> <td></td> </tr> <tr> <td>4</td> <td>BLUE / White</td> <td>RED</td> <td></td> </tr> <tr> <td>5</td> <td>WHITE / Orange</td> <td>BLACK</td> <td></td> </tr> <tr> <td>6</td> <td>White / Green</td> <td>NOT USED</td> <td></td> </tr> <tr> <td>7</td> <td>NOT USED</td> <td>NOT USED</td> <td></td> </tr> <tr> <td>8</td> <td>NOT USED</td> <td>NOT USED</td> <td></td> </tr> </tbody> </table>	Pin	Color	Wire Color	Other Colors	1	GREEN / White	BLUE		2	ORANGE / White	YELLOW		3	WHITE / Blue	GREEN		4	BLUE / White	RED		5	WHITE / Orange	BLACK		6	White / Green	NOT USED		7	NOT USED	NOT USED		8	NOT USED	NOT USED		 <p><b>Hamilton®</b> SHEER CFX 2J12 2 gang RJ12 Outlet Unshielded 6 wire</p>
Pin	Color	Wire Color	Other Colors																																			
1	GREEN / White	BLUE																																				
2	ORANGE / White	YELLOW																																				
3	WHITE / Blue	GREEN																																				
4	BLUE / White	RED																																				
5	WHITE / Orange	BLACK																																				
6	White / Green	NOT USED																																				
7	NOT USED	NOT USED																																				
8	NOT USED	NOT USED																																				
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.																																					
Insert Type	2 gang RJ12 Outlet - Unshielded																																					
Plate Finish	Sheer CFX Black Nickel																																					
Insert Colour	Black																																					
EAN13 Barcode	5017504051563																																					
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket																																					
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips																																					
Minimum Wall Box Depth	35mm																																					
Switched Poles	N/A																																					
IP Rating	IP2XD																																					
Contact Gap Minimum	N/A																																					
Earth Terminal Capacity 1	5 x 1mm <sup>2</sup>																																					
Earth Terminal Capacity 2	4 x 1.5mm <sup>2</sup>																																					
Earth Terminal Capacity 3	3 x 2.5mm <sup>2</sup>																																					
Earth Terminal Capacity 4	1 x 4mm <sup>2</sup> Multi-strand																																					
Earth Terminal Capacity 5	1 x 6mm <sup>2</sup>																																					
Product Class 1	Must be earthed (ref BS7671 415.2.1)																																					
Ambient Operating Temperature	-5° to +40°C																																					
Recommended Location	Internal Use Only																																					
Maximum Installation Altitude	2000m																																					
EuroFix Additional Notes	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)																																					
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755																																					
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.																																				
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:42 AM E&OE																																				

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84

