Item Image

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

88CR22BK-B

Sheer CFX Black Nickel 2 gang 10AX 2 Way Rocker Black Nickel/Black

Wiring

Hamilton R22 2 Way Rocker Primary Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. Insert Type 2 gang 10AX 2 Way Rocker Plate Finish Sheer CFX Black Nickel Insert Colour Black Nickel/Black EAN13 Barcode 5017504052225 Dimensions (Nominal) Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 25mm Switched Poles Single **Current Rating** 10AX 220/250V AC Voltage 10 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 **Terminal Capacity 3** 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

All accessories are manufactured under an accredited

CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586

Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755

It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Correct as at 17 October 2018 10:43 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Ambient Operating Temperature

Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Standard/Approval

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

-5° to +40°C Internal Use Only

BS EN 60669-1

2000m















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio