SL



making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

88CRRTBK-B

Sheer CFX Black Nickel 1 gang 10AX Push To Make/Push to Break Retractive Rocker Black Nickel/Black


Primary Range

Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that cooling Insert Type

1 gang 10AX Push To Make/Push to Break Retractive Rocker

Plate Finish
Insert Colour
Black Nickel
Insert Colour
Black Nickel/Black

5017504052195



Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure	s that comply with BS4662-2006.
Insert Type	1 gang 10AX Push To Make/Push to Break Retractive Rocker	
Plate Finish	Sheer CFX Black Nickel	
Insert Colour	Black Nickel/Black	
EAN13 Barcode	5017504052195	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	10AX	
Voltage	220/250V AC	
Maximum Load	10 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	1 x 2.5mm2	
Terminal Capacity 4	1 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	5 x 1mm2	
Earth Terminal Capacity 2	4 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior police.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84







and dimensions without prior notice.



Correct as at 17 October 2018 10:43 AM E&OE







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio