making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


88CSS2BK-B

Sheer CFX Black Nickel 2 gang 13A Double Pole Switched Socket Black Nickel/Black


Item Image



Wiring



Dimensions



Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.	
Insert Type	2 gang 13A Double Pole Switched Socket	
Plate Finish	Sheer CFX Black Nickel	
Insert Colour	Black Nickel/Black	
EAN13 Barcode	5017504052027	
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket	
Weight	254 GR	
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Double	
Current Rating	13 Amp	
Voltage	220/250V AC	
Maximum Load	13 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	4 x 2.5mm2	
Terminal Capacity 2	3 x 4mm2	
Terminal Capacity 3	2 x 6mm2 Multi-Strand	
Terminal Capacity 4	1 x 10mm2	
Earth Terminal Capacity 1	4 x 2.5mm2	
Earth Terminal Capacity 2	3 x 4mm2	
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand	
Earth Terminal Capacity 4	1 x 10mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS 1363-2	
Additional Notes	Dual Earth: Yes	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes	Correct as at 17 October 2018 10:43 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

0414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB on-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84

















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio