SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


88DPNBK-B

Sheer Black Nickel 1 gang 20AX Double Pole Rocker and Neon Black Nickel/Black


Item Image







Dimensions



Primary Range	Sheer		
Insert Type	1 gang 20AX Double Pole Rocker + Neon		
Plate Finish	Sheer Box Black Nickel		
Insert Colour	Black Nickel/Black		
EAN13 Barcode	5017503882946		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5n	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm	
Weight	150 GR		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A		
Minimum Wall Box Depth	35mm		
Switched Poles	Double		
Current Rating	20AX		
Voltage	220/250V AC		
Maximum Load	20 Amp inductive		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	3 x 2.5mm2		
Terminal Capacity 2	2 x 4mm2 Multi Strand		
Terminal Capacity 3	1 x 6mm2		
Earth Terminal Capacity 1	6 x 1mm2		
Earth Terminal Capacity 2	5 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-1		
Patents and Trademarks	Sheer is a Registered Trade Mark No. 2296586		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 17 October 2018 10:02 AM E&OE	

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











