## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio
	<u>88TRT</u>	
Sheer Dlock Nickel 1a		tive Teagle Block Nickel
Sheer Black Nickel Tg	10AX Push To Make/Push To Break Retract	
Item Image	Wiring	Dimensions
		Hamilton
		Hemilton SHeer Tr Push to Make/Push to Break Retractive Toggle
Primary Range	Sheer	
Insert Type	1 gang 10AX Push To Make/Push To Break Retractive Toggle	
Plate Finish	Sheer Box Black Nickel	
Insert Colour	Black Nickel	
EAN13 Barcode	5028690882909	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm	
Switched Poles	Single	
Current Rating	10AX	
Voltage	220/250V AC	
Maximum Load	10 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 1	5 x 1.5mm2	
	3 x 2.5mm2	
Earth Terminal Capacity 3 Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
	1 x 6mm2	
Earth Terminal Capacity 5 Product Class 1	Must be earthed	
	-5° to +40°C	
Ambient Operating Temperature		
Recommended Location	Internal Use Only 2000m	
Maximum Installation Altitude	BS EN 60669-1	
Standard/Approval	BS EN 60669-1 Sheer is a Registered Trade Mark No. 2296586	
Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:02 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O E: info@hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Primile Product Selector Display (CRI No. FM128)