

# making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 892X2V


Sheer Antique Brass 2 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Antique Brass

Item Image

## Wiring



### Dimensions



Primary Range	Sheer		
Insert Type	2 gang 200VA Inductive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers		
Plate Finish	Sheer Box Antique Brass		
Insert Colour	Antique Brass		
EAN13 Barcode	5017503899128		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	Box Fixing = 60.3mm Grid Fixing = N/A	
Minimum Wall Box Depth	35mm		
Wattage	200VA (low voltage) per gang		
Switched Poles	Single		
Current Rating	0.8 Amp		
Voltage	220/250V AC		
Maximum Load	200VA per gang (low voltage) Min Load 25VA		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	None		
Terminal Capacity 1	2 x 1mm2		
Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-1		
Additional Notes	LEADING EDGE TECHNOLOGY DIMMERS for use with low voltage toroidal transformers and some LED lamps. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. NOTE:It is recommended to contact the manufacturer of the transformer to confirm that it is dimmable and is considered to be an inductive load.		
Patents and Trademarks	Sheer is a Registered Trade Mark No. 2296586		
All products listed conform to current British or European standard and the product information is	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.	

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.







Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 17 October 2018 10:02 AM







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio