Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sr	mart Lighting Control & Multi-room Audio	
	89CDTVFB		
Sheer CF	X Antique Brass 1 gang Non-Isolated TV (fer	male) Black	
Item Image	Wiring	Dimensions	
$\overline{}$	EMC Gasket Conductor Terminal Screw Correct position of conductor, screening braid and cable	HEER CFX DTVF Non-Isolated TV (female)	
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.		
Insert Type	1 gang Non-Isolated TV (female) (DAB Compatible)		
Plate Finish	Sheer CFX Antique Brass		
Insert Colour	Black		
EAN13 Barcode	5017504061531		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	N/A		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed (ref BS7671 415.2.1)		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only	Internal Use Only	
Maximum Installation Altitude	2000m		
EuroFix Additional Notes	TV Outlet (IEC 169-2 Female Socket) Usually used for FM (DAB) outlet		
Frequencies 1	TV DC=5-2200 MHz		
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:43 AM E&Ol	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com	Road, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB in London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble, product selector	