Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sm	nart Lighting Control & Multi-room Audio
	<u>89CT21</u>	
Sheer CFX Antique Brass 1 gang 20AX 2 Way Toggle Antique Brass		
Item Image	Wiring	Dimensions
	Image: second	Hemilton SHEER CFX T21 2 Way Toggle
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.	
Insert Type	1 gang 20AX 2 Way Toggle	
Plate Finish	Sheer CFX Antique Brass	
Insert Colour	Antique Brass	
EAN13 Barcode	5017504062255	
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
Minimum Wall Box Depth	35mm	
Switched Poles	Single	
Current Rating	20AX	
Voltage	220/250V AC	
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	3mm 5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 2	2 x 2.5mm2	
	2 x 2:smm2 2 x 4mm2 Multi-strand	
Terminal Capacity 4		
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:43 AM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Rr T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered C E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	Dad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Strimble product Selector Strimble CRE No. 1ML 2007

SL

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio