



89CTCMB

Sheer CFX Antique Brass 1 gang Telephone Master Black

Item Image	Wiring	Dimensions														
	<table border="1" data-bbox="662 472 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule Colour Codes:</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Striped Wires GREEN / White</td> </tr> <tr> <td>2</td> <td>BLUE / White</td> </tr> <tr> <td>3</td> <td>ORANGE / White</td> </tr> <tr> <td>4</td> <td>WHITE / Orange</td> </tr> <tr> <td>5</td> <td>WHITE / Blue</td> </tr> <tr> <td>6</td> <td>WHITE / Green</td> </tr> </tbody> </table> <p data-bbox="673 604 953 661">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 613 915 661">Incoming Telephone Cable On 4 wire systems, Pin 1 and 6 are not connected.</p> <p data-bbox="662 688 964 766">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p>	Pin No.	BT Wiring Schedule Colour Codes:	1	Striped Wires GREEN / White	2	BLUE / White	3	ORANGE / White	4	WHITE / Orange	5	WHITE / Blue	6	WHITE / Green	<p data-bbox="1234 451 1396 535">Hamilton® SHEER CFX TCM Telephone Master Socket</p> 
Pin No.	BT Wiring Schedule Colour Codes:															
1	Striped Wires GREEN / White															
2	BLUE / White															
3	ORANGE / White															
4	WHITE / Orange															
5	WHITE / Blue															
6	WHITE / Green															
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.															
Insert Type	1 gang Telephone Master															
Plate Finish	Sheer CFX Antique Brass															
Insert Colour	Black															
EAN13 Barcode	5017504061647															
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket															
Weight	136 GR															
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips															
Minimum Wall Box Depth	25mm															
Switched Poles	N/A															
IP Rating	IP2XD															
Contact Gap Minimum	N/A															
Earth Terminal Capacity 1	5 x 1mm ²															
Earth Terminal Capacity 2	4 x 1.5mm ²															
Earth Terminal Capacity 3	3 x 2.5mm ²															
Earth Terminal Capacity 4	1 x 4mm ² Multi-strand															
Earth Terminal Capacity 5	1 x 6mm ²															
Product Class 1	Must be earthed (ref BS7671 415.2.1)															
Ambient Operating Temperature	-5° to +40°C															
Recommended Location	Internal Use Only															
Maximum Installation Altitude	2000m															
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755															
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.														
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:43 AM E&OE														

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84



CERT. No. FM11238