making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

8EBC3X40

Sheer CFX Etrium Bronze 3x400W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmers Etrium Bronze			
Item Image	Wiring	Dimensions	
	Drimmer Welving Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Use Negford Loop In Loop Cut. Two Welly Switching Loop In Loop Cut. Two Well Switching Loop Cut. Two We	Hemilton SHEER CFX 3X40 Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer	
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.	
Insert Type	3 gang 400w Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer		
Plate Finish	Sheer CFX Etrium Bronze		
Insert Colour	Etrium Bronze		
EAN13 Barcode	5017504027490		
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket		
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Wattage	400W per gang		
Switched Poles	Single		
Current Rating	1.66 Amps per gang		
Voltage	220/250V AC		
Maximum Load	400W resistive per gang		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Terminal Capacity 1	2 x 1mm2		
Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility.		
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:44 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio