Hamilton

making connections beautifully

SL

Primary Range

Insert Type

Plate Finish

Insert Colour

EAN13 Barcode Dimensions (Nominal)

Fixing Hole Centres

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 8HBC3XTMAB-B Sheer CFX Connaught Bronze 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Black Nickel/Black Item Image Wiring Dimensions Hamilton SHEER CFX 3XTM tive Trailing Edge Touch Master Multi-Way Dimmer Multi- Way Wiring using Slave module(s) ⇒ Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. 3 gang 250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmer Sheer CFX Connaught Bronze Black Nickel/Black 5017504028282 Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket Box Fixing = 120.6mm Grid Fixing = CFX Clips 35mm

| 5 | | |
|-------------------------------|--|--|
| Minimum Wall Box Depth | 35mm | |
| Wattage | 250W Resistive 210VA Inductive | |
| Switched Poles | N/A | |
| Current Rating | 1.1 Amps per gang | |
| Voltage | 220/250V AC | |
| Maximum Load | 250W Resistive per gang 210VA Inductive Min Load 25W/25VA | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | N/A | |
| Terminal Capacity 1 | 2 x 1mm2 | |
| Terminal Capacity 2 | 2 x 1.5mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Face plate must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-2-1 | |
| Additional Notes | TRAILING EDGE TECHNOLOGY DIMMERS. Are suitable for control of both resistive and inductive loads. When used for dimming low voltage electronic halogen transformers it must be noted that the dimmer controls the primary side of the transformer. Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. When using mains voltage halogen load transformer - maximum rating is 210VA. NOTE: For multi-way switching a push to make retractive switch should be installed in the other positions. (Note:standard two way switches will not work with this product) | |
| | | |

Hamilton

making connections beautifully

Wining Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

8HBC3XTMAB-B

Sheer CFX Connaught Bronze 3x250W/210VA Resistive/Inductive Trailing Edge Touch Master Multi-Way Dimmers Black Nickel/Black

| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755 | | |
|---|--|--|--|
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 10:44 AM E&OE | |
| | ad, Brislington, Bristol, BS4 5NZ ice 1 Rushmills, Bedford Road, Northampton NN4 7YB ondon No. 941624 VAT Registration No. 222 6607 84 | Listed in STrimble product selector | |

SL