SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

8PNCSS1USBBC-B

Sheer CFX Polished Nickel 1 gang 13A Single Pole Switched Socket with 1 USB Outlets 1x2.1A Bright Chrome/Black

| Sheer CFX Polished Nickel 1 gang 13A Single Pole Switched Socket with 1 USB Outlets 1x2.1A Bright Chrome/Black | | |
|---|---|--|
| Item Image | Wiring | Dimensions Hemilton SHEER CFX SS1USBX1 USB Charger + Switched Socket |
| | | 86.0 4.5 21.7 |
| Primary Range | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. | |
| Insert Type | 1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A | |
| Plate Finish | Sheer CFX Polished Nickel | |
| Insert Colour | Bright Chrome/Black | |
| EAN13 Barcode | 5017504089719 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Single | |
| Current Rating | 13 Amp, USB = 2.1A | |
| Voltage | 180/250V AC | |
| Maximum Load | 13 Amp, USB = 2.1A | |
| Mains Frequency | 50/60Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 2.5mm2 | |
| Terminal Capacity 2 | 3 x 4mm2 | |
| Terminal Capacity 3 | 2 x 6mm2 Multi-Strand | |
| Earth Terminal Capacity 1 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 2 | 3 x 4mm2 | |
| Earth Terminal Capacity 3 | 2 x 6mm2 Multi-strand | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -15°C to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS1363, BS5733, EN60950-1 | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 10:45 AM E&OE |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)17179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84









