Hamilton

making connections beautifully

| | Wiring Accessories • Circuit Protection • Sr | nart Lighting Control & Multi-room Audio |
|--|---|--|
| | 8RBCUS5B | |
| | | |
| Sheer CFX Richmond Bronze 1 gang 5A Unswitched Socket Black | | |
| Item Image | Wiring | Dimensions |
| | Neutral Earth Live | Hemilton SHEER CFX US5 Unswitched Socket |
| | | |
| Primary Range | Sheer CFX - Designed to fit Folded Metal Wall Box Enclosure | es that comply with BS4662-2006. |
| Insert Type | 1 gang 5A Unswitched Socket | |
| Plate Finish | Sheer CFX Richmond Bronze | |
| Insert Colour | Black | |
| EAN13 Barcode | 5017504030544 | |
| Dimensions (Nominal) | Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = CFX Clips | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | None | |
| Current Rating | 5 Amp | |
| | 220/250V AC | |
| Voltage Maximum Load | 5 Amp | |
| | | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | None | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 1 x 4mm2 | |
| Earth Terminal Capacity 1 | 5 x 1mm2 | |
| Earth Terminal Capacity 2 | 4 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 2 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 1 x 4mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS 546 | |
| Additional Notes | Shuttered: Yes | |
| Patents and Trademarks | CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 17 October 2018 10:45 A E&C |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville R T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered C E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | Dad, Brislington, Bristol, BS4 5NZ Iffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimble product selector DSSPUs (Ext. Iso. IMI228 |

SL