

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

8RBSHSB

the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of of certain finishes.	Sheer Richmond Bron	<u>8RBSHSB</u> ze Shaver Dual Voltage Unswitched Socket (V	ertically Mounted) Black	
Primary Range Sheer Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Cocker Share Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Cocker Share Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Insert Cocker Share Sha	Item Image	Wiring	Dimensions	
Insert Type Shaver Dual Voltage Unswitched Socket (Vertically Mounted) Plate Finish Sheer Box Vertical Richmond Bronze Black EAN13 Barcode 5017504033279 Dimensions (Nominal) Double: Height = 146.0mm Width = 86.0mm Depth = 1.5mm Fining Hole Centres Box Fising = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 47mm Switched Poles Current Rating 20VA Voltage 220/250V AC Voltage 220/250V AC Waximum Load Maximum Load Maximum Load Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 5 x 2.5mm2 Earth Terminal Capacity 3 5 x 1.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1 x 6mm2 Earth Terminal Capacity 9 5 x 1 x 6mm2 Earth Termi			SHS Shaver Dual Voltage Unswitched Socket (Vertical Mounted) 15. 46.0 120.6 120.6	
Plate Finish Insert Colour Black EAN13 Barcode 5017504033279 Dimensions (Nominal) Double: Height = 146.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 4/mm Switched Poles None Current Rating 20VA Voltage 220250V AC Maximum Load 200250V input; 115/230V 20VA output Mains Frequency Fixing Hole Fixing	Primary Range	Sheer		
Insert Colour EAN13 Barcode 5017504033279 Dimensions (Nominal) Double: Height = 146 0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220250V AC Walkarum Load 200250V input; 115/230V 20VA output Mains Frequency FP Rating P2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 1 Ferminal Capacity 1 Searth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal	Insert Type	Shaver Dual Voltage Unswitched Socket (Vertically Mounted)		
EAN13 Barcode 5017504033279 Dimensions (Nominal) Double: Height = 146.0mm Width = 86.0mm Depth = 1.5mm Fixing Holo Centres 80x Fixing + 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20vA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency IP Rating IP2XD Contact Gap Minimum None Firminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 1 x 6mm2 Earth Terminal Capacity 7 5 1 x 6mm2 Earth Terminal Capacity 8 5 1 x 6mm2 Earth Terminal Capacity 9	Plate Finish	Sheer Box Vertical Richmond Bronze		
Dimensions (Nominal) Double: Height = 146.0mm Width = 86.0mm Depth = 1.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency IP Rating IP ZXD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 5 x 1mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 3 5 x 1mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Ca	Insert Colour	Black		
Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A	EAN13 Barcode	5017504033279		
Minimum Wall Box Depth 47mm Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz PRating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 x 1.5mm2 Earth Terminal Capacity 7 9 x 1mm2 Earth Terminal Capacity 8 1 x 6mm2 Earth Terminal Capacity 9 5 x 1mm2 Earth Terminal Capacity 9 6 x 1.5mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x 6mm2 Earth Termi	Dimensions (Nominal)	Double: Height = 146.0mm Width = 86.0mm Depth = 1.5mm		
Switched Poles None Current Rating 20VA Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Terminal Capacity 5 4 x 1.5mm2 Terminal Capacity 6 6 x 1.5mm2 Terminal Capacity 7 5 x 1mm2 Terminal Capacity 8 7 x 6mm2 Terminal Capacity 9 7 x 6mm2 Terminal Capacity 9 x 7 x 6mm2 Terminal	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A		
Current Rating 20VA Cottage 220/250V AC 200/250V input; 115/230V 20VA output 200/250V	Minimum Wall Box Depth	47mm		
Voltage 220/250V AC Maximum Load 200/250V input; 115/230V 20VA output Maxins Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 5 x 4 mm2 Multi-strand Earth Terminal Capacity 4 5 x 4 mm2 Multi-strand Earth Terminal Capacity 5 5 1 x 6mm2 Earth Terminal Capacity 6 5 1 x 6mm2 Earth Terminal Capacity 7 5 x 4 x 6 x 5 x 6 x 7 x 6 x 7 x 7 x 7 x 7 x 7 x 7 x 7	Switched Poles	None		
Maximum Load 200/250V input; 115/230V 20VA output Mains Frequency 50Hz IP Rating IP 2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 5 x 1.5mm2 Earth Terminal Capacity 1 2 x 4mm2 Multi-strand Earth Terminal Capacity 2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 In x 6mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 9 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 9 Earth Ter	Current Rating	20VA		
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 3 1 x 6mm2 Forduct Class 1 1 x 6mm2 Froduct Class 1 1 Must be earthed Ambient Operating Temperature 5° to 440°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered : Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or European standard and the product information is correct at the time of going to press. BALL Products listed conform to current British or European standard and the product information is correct at the time of going to press.	Voltage	220/250V AC		
IP Rating	Maximum Load	200/250V input; 115/230V 20VA output		
Contact Gap Minimum None Terminal Capacity 1 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 6 Earth Terminal Capacity 8 Earth Terminal Capacity 9 E	Mains Frequency	50Hz		
Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1	IP Rating	IP2XD		
Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 In x 6mm2 Earth Terminal Capacity 5 Todacity 4 Earth Terminal Capacity 5 In x 6mm2 Froduct Class 1 Ambient Operating Temperature So to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. Billustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of process and are not binding, Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Contact Gap Minimum	None		
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 In 6 mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Standard/Approval Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding.	Terminal Capacity 1	5 x 1mm2		
Terminal Capacity 4 2 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 6 Earth Terminal Capacity 7 Earth Terminal Capacity 8 Earth Terminal Capacity 9	Terminal Capacity 2	4 x 1.5mm2		
Terminal Capacity 5	Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 1 9 x 1mm2 Earth Terminal Capacity 2 6 x 1.5mm2 Earth Terminal Capacity 3 4 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited European standard and the product information is correct at the time of going to press. BILUstrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Terminal Capacity 4	2 x 4mm2 Multi-strand		
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Must be mounted vertically. Shuttered: Yes. Box Depth 47mm Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. BEN ISO 9001: 2015 Quality Management System. BUDE to manufacturing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Correct as at 17 October 2018 10:03 A E&C	Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. But to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 1	9 x 1mm2		
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes Must be mounted vertically. Shuttered: Yes. Box Depth 47mm Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System. BIIlustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Earth Terminal Capacity 2	6 x 1.5mm2		
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:03 A ESC	Earth Terminal Capacity 3	4 x 2.5mm2		
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval Additional Notes BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered: Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BIllustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:03 A ESC	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand		
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks All products listed conform to current British or European standard and the product information is correct at the time of going to press. All products listed conform to current British or BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Due to manufacturing processes we cannot the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	Earth Terminal Capacity 5	1 x 6mm2		
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. Correct as at 17 October 2018 10:03 A E&C	Product Class 1	Must be earthed		
Maximum Installation Altitude 2000m Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:03 A E&C	Ambient Operating Temperature	-5° to +40°C		
Standard/Approval BS EN 61558-2-5 - BS 4573 Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing processes we cannot guarantee an exact colour match and shadings of process and are not binding. BS EN 61558-2-5 - BS 4573 Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Sheer is a Registered Trade Mark No. 2296586 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10:03 A E&C grant finishes.	Recommended Location	Internal Use Only		
Additional Notes Must be mounted vertically. Shuttered :Yes. Box Depth 47mm Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10:03 A E&C	Maximum Installation Altitude	2000m		
Patents and Trademarks Sheer is a Registered Trade Mark No. 2296586 All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. But is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Standard/Approval	BS EN 61558-2-5 - BS 4573		
All products listed conform to current British or European standard and the product information is correct at the time of going to press. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Correct as at 17 October 2018 10:03 A E&C guarantee an exact colour match and shadings of of certain finishes.	Additional Notes	Must be mounted vertically. Shuttered :Yes. Box Depth 47mm		
European standard and the product information is correct at the time of going to press. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 17 October 2018 10:03 A E&C of certain finishes.	Patents and Trademarks	Sheer is a Registered Trade Mark No. 2296586	Sheer is a Registered Trade Mark No. 2296586	
the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding. guarantee an exact colour match and shadings of certain finishes.	European standard and the product information is		as part of our development programme. Therefore, we reserve the right to alter designs	
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ	the limitations of reproduction and printing process and are not binding.	guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:03 AM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio