




## 8WPC2J12B

### Sheer CFX Primed White 2 gang RJ12 Outlet - Unshielded Black

Item Image	Wiring	Dimensions
		
<b>Primary Range</b>	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.	
<b>Insert Type</b>	2 gang RJ12 Outlet - Unshielded	
<b>Plate Finish</b>	Sheer CFX Primed White	
<b>Insert Colour</b>	Black	
<b>EAN13 Barcode</b>	5017504030759	
<b>Dimensions (Nominal)</b>	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket	
<b>Fixing Hole Centres</b>	Box Fixing = 60.3mm Grid Fixing = CFX Clips	
<b>Minimum Wall Box Depth</b>	35mm	
<b>Switched Poles</b>	N/A	
<b>IP Rating</b>	IP2XD	
<b>Contact Gap Minimum</b>	N/A	
<b>Earth Terminal Capacity 1</b>	5 x 1mm <sup>2</sup>	
<b>Earth Terminal Capacity 2</b>	4 x 1.5mm <sup>2</sup>	
<b>Earth Terminal Capacity 3</b>	3 x 2.5mm <sup>2</sup>	
<b>Earth Terminal Capacity 4</b>	1 x 4mm <sup>2</sup> Multi-strand	
<b>Earth Terminal Capacity 5</b>	1 x 6mm <sup>2</sup>	
<b>Product Class 1</b>	Must be earthed (ref BS7671 415.2.1)	
<b>Ambient Operating Temperature</b>	-5° to +40°C	
<b>Recommended Location</b>	Internal Use Only	
<b>Maximum Installation Altitude</b>	2000m	
<b>EuroFix Additional Notes</b>	Can be used as either RJ11 (4 wires) or RJ12 (6 wires)	
<b>Patents and Trademarks</b>	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 =3020755	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:45 AM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84

