SL

Product Class 1

Ambient Operating Temperature

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Standard/Approval

Item Image

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

8WPC45SS1WH-W

Sheer CFX Primed White 45A Double Pole Rocker + Neon + 13A Switched Socket Red+White/White

Wiring

Hemilton
SHER CFX
45SS1
Double Pole Red Rocker & Noor
13A Switched Socket

	Manual Ma
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.
Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socket
Plate Finish	Sheer CFX Primed White
Insert Colour	Red+White/White
EAN13 Barcode	5017504030865
Dimensions (Nominal)	Double: Height = 86.0mm Width = 145.0mm Depth = 1.5mm plate + 3.0mm gasket
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Double
Current Rating	Switch 45 Amp Socket 13 Amp
Voltage	220/250V AC
Maximum Load	Switch 45 Amp Socket 13
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	3 x 6mm2
Terminal Capacity 2	2 x 10mm2
Terminal Capacity 3	1 x 16mm2
Earth Terminal Capacity 1	3 x 6mm2
Earth Terminal Capacity 2	2 x 10mm2
Earth Terminal Capacity 3	1 x 16mm2

CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586

All accessories are manufactured under an accredited

BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755

the limitations of reproduction and printing guarantee an exact colour match and shadings of process and are not binding.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered in London No. 941624 VAT Registration No. 222 6607 84

Must be earthed

-5° to +40°C Internal Use Only

2000m

BS 4177









It is the policy of the company to improve products

as part of our development programme.

Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 17 October 2018 10:46 AM



E&OE