SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio **8WPCFNBL-R** Sheer CFX Primed White 1 gang 13A Fuse with Neon Halo Black/Red Item Image Wiring **Dimensions** Hamilton SHEER CFX Primary Range Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006. Insert Type 1 gang 13A Fuse with Red Neon Halo Plate Finish Sheer CFX Primed White Insert Colour Black/Red EAN13 Barcode 5017504031152 Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket Dimensions (Nominal) Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = CFX Clips Minimum Wall Box Depth 35mm Switched Poles None **Current Rating** 13 Amp 220/250V AC Voltage Maximum Load 13 Amp Mains Frequency 50Hz IP2XD IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2 5mm2 Terminal Capacity 2 2 x 4mm2 Multi Strand **Terminal Capacity 3** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed -5° to +40°C **Ambient Operating Temperature** Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 5733 with Fuselink to BS1362 CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Patents and Trademarks Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. as part of our development programme correct at the time of going to press Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 17 October 2018 10:46 AM guarantee an exact colour match and shadings of the limitations of reproduction and printing E&OE process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











