SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

8WPCSS1USBWH-W

Sheer CFX Primed White 1 g	ang 13A Single Pole Switched Socket with 1 I	USB Outlets 1x2.1A White/White	
Item Image	Wiring	Dimensions	
		Hemilton SHEER CFX SS1USBX1 USB Charger + Switched Socket	
		86.0 45 21.7 4	
Primary Range	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosur	Sheer CFX - Designed to fit Folded Metal Wall Box Enclosures that comply with BS4662-2006.	
Insert Type	1 gang 13A Single Pole Switched Socket with 1 USB Outlet 1x2.1A		
Plate Finish	Sheer CFX Primed White		
Insert Colour	White/White		
EAN13 Barcode	5017504089764		
Dimensions (Nominal)	Single: Height = 86.0mm Width = 86.0mm Depth = 1.5mm plate + 3.0mm gasket		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips		
Minimum Wall Box Depth	35mm		
Switched Poles	Single		
Current Rating	13 Amp, USB = 2.1A		
Voltage	180/250V AC		
Maximum Load	13 Amp, USB = 2.1A		
Mains Frequency	50/60Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	3 x 2.5mm2		
Terminal Capacity 2	3 x 4mm2		
Terminal Capacity 3	2 x 6mm2 Multi-Strand		
Earth Terminal Capacity 1	3 x 2.5mm2		
Earth Terminal Capacity 2	3 x 4mm2		
Earth Terminal Capacity 3	2 x 6mm2 Multi-strand		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-15°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS1363, BS5733, EN60950-1		
Patents and Trademarks	CFX is a Registered Trade Mark No 2398667 Trade Mark No. 2296586 Sheer CFX is a Registered Design under Reference Nos. R21 = 3020754 SS2 = 3020755		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 17 October 2018 10:46 AM E&OE	
	-		

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ
T: +44 (0)1747 860088 F: +44 (0)17179 710414
E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB
Registered in London No. 941624 VAT Registration No. 222 6607 84









