## Hamilton

## making connections beautifully

|  | Wiring Accessories • Circuit Protection • Sr   | mart Lighting Control & Multi-room Audio   |
|--|--|--|
|  |  |  |
| <u>904XTSPB-B</u>  |  |  |
| Cheriton Georgian Polished Brass 4 gang Multi-Way Touch Slave Controller Polished Brass/Black  |  |  |
| Item Image   | Wiring   | Dimensions   |
| Summunumunum   | Multi- Way Wiring using Slave module(s)  | Hemilton<br>CHERITON GEORGIAN<br>4XTS<br>Multi-WayTouch Slave Controller   |
|  | LIVE SLAVE MODULE SLAVE MODULE<br>ONLY ONE MASTER MODULE IS UBED PER GRCUIT.   |  |
| Primary Range  | Cheriton   |  |
| Insert Type  | 4 gang Multi-Way Touch Slave Controller  |  |
| Plate Finish   | Cheriton Georgian GRID-IT Polished Brass   |  |
| Insert Colour  | Polished Brass/Black   |  |
| EAN13 Barcode  | 5028690351450  |  |
| Dimensions (Nominal)   | Double: Height = 86.5mm Width = 146.0mm Depth = 10.5mm   |  |
| Fixing Hole Centres  | Box Fixing = 120.6mm Grid Fixing = 106.5mm   |  |
| Minimum Wall Box Depth   | 35mm   |  |
| Wattage  | The same as Touch Master or Ceiling Dimmer   |  |
| Switched Poles   | N/A  |  |
| Current Rating   | The same as Touch Master or Ceiling Dimmer   |  |
| Voltage  | 220/250V AC  |  |
| Maximum Load   | The same as Touch Master   |  |
| Mains Frequency  | 50Hz   |  |
| IP Rating  | IP2XD  |  |
| Contact Gap Minimum  | N/A  |  |
| Terminal Capacity 1  | 2 x 1mm2   |  |
| Terminal Capacity 2  | 2 x 1.5mm2   |  |
| Earth Terminal Capacity 1  | 5 x 1mm2   |  |
| Earth Terminal Capacity 2  |  |  |
| Earth Terminal Capacity 3  | 4 x 1.5mm2<br>3 x 2.5mm2   |  |
|  | 1 x 4mm2 Multi-strand  |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand<br>1 x 6mm2  |  |
| Earth Terminal Capacity 5  | Face plate must be earthed   |  |
| Product Class 1  |  |  |
| Ambient Operating Temperature  | -5° to +40°C   |  |
| Recommended Location   | Internal Use Only  |  |
| Maximum Installation Altitude  | 2000m  |  |
| Standard/Approval Additional Notes   | BS EN 60669-2-1<br>Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers<br>should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be<br>used with Touch Master Dimmers |  |
| Patents and Trademarks   | Cheriton is a Registered Trade Mark No. 2344779  |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.  | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.   | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.   | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.  | Correct as at 12 October 2018 04:40 PN<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ<br>T: +44 (0)1747 860088 F: +44 (0)179 710414<br>E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>Registered office 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>Registered in London No. 941624 VAT Registration No. 222 6607 84 |  |  |

Hamilton

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio