SL

Item Image

## making connections beautifully

**Dimensions** 

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 904XTSPB-W

Cheriton Georgian Polished Brass 4 gang Multi-Way Touch Slave Controller Polished Brass/White

Wiring

Hamilton 4XTS
Multi-WayTouch Slave Controller Multi- Way Wiring using Slave module(s) Primary Range Cheriton Insert Type 4 gang Multi-Way Touch Slave Controller Plate Finish Cheriton Georgian GRID-IT Polished Brass Insert Colour Polished Brass/White EAN13 Barcode 5028690350453 Dimensions (Nominal) Double: Height = 86.5mm Width = 146.0mm Depth = 10.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = 106.5mm Minimum Wall Box Depth 35mm Wattage The same as Touch Master or Ceiling Dimmer Switched Poles N/A Current Rating The same as Touch Master or Ceiling Dimmer 220/250V AC Voltage Maximum Load The same as Touch Master 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed

process and are not binding. R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

**Ambient Operating Temperature** 

Maximum Installation Altitude

Recommended Location

Patents and Trademarks

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

Standard/Approval

Additional Notes

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

-5° to +40°C

2000m

Internal Use Only

BS EN 60669-2-1

should be de-rated by 25%. used with Touch Master Dimmers

Cheriton is a Registered Trade Mark No. 2344779

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes



Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps-dimmers



When using mains voltage halogen load transformer - maximum rating is 210VA. To only be



It is the policy of the company to improve products

as part of our development programme Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 12 October 2018 04:40 PM







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio