

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


90FOCBL-B

Cheriton Georgian Polished Brass 1 gang 13A Fuse and Cable Outlet Black/Black


Item Image



Wiring



Dimensions



Primary Range			Ø11.0
Plate Finish	Primary Range	Cheriton	
Black/Black	Insert Type	1 gang 13A Fuse + Cable Outlet	
EAN13 Barcode	Plate Finish	Cheriton Georgian Box Polished Brass	
Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 10.5mm	Insert Colour	Black/Black	
Fixing Hole Centres	EAN13 Barcode	5017503351961	
Minimum Wall Box Depth 35mm Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz P Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Earth Terminal Capacity 7 Earth Terminal Capacity 8 2 x 4mm2 Multi-strand Earth Terminal Capacity 9 1 x 6mm2 Earth Terminal Capacity 9	Dimensions (Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 10.5mm	
Switched Poles None Current Rating 13 Amp Voltage 220/250V AC Maximum Load 13 Amp Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1 mm2 Terminal Capacity 1 5 x 1 mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 5 x 1.5mm2 Earth Terminal Capacity 7 5 x 1.5mm2 Earth Terminal Capacity 8 5 x 1.5mm2 Earth Terminal Capacity 9 5 x 1.5mm2 Earth Terminal Capacity 1 6 x 1 mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature 5.5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is 8 ES 180 S001: 2010 Juelly Manager an accredied 8 ES 180 S001: 2010 Juelly Manager and seried as part of our development programme.	Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Current Rating	Minimum Wall Box Depth	35mm	
Voltage	Switched Poles	None	
Maximum Load	Current Rating	13 Amp	
Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 6 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature 5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current Britsh or European standard and the product information is BS EN ISS 9001 : 2015 Caudity System. It is the policy of the company to improve products as part of our development programme.	Voltage	220/250V AC	
IP Rating IP2XD Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Froduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. All products listed conform to current British or European standard and the product information is BS EN ISO 9001: 2015 Quality Management System. All accessories are manufactured under an accredited as a part of our development programme.	Maximum Load	13 Amp	
Contact Gap Minimum None Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Farth Terminal Capacity 6 1 x 6mm2 Forduct Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN 1805 2001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Mains Frequency	50Hz	
Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 3 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 1 6 x 1.5mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is SE NE ISS 9001 : 2015 Quality Management System. Is separated or the decompany to improve products as a part of our development programme.	IP Rating	IP2XD	
Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 5 Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 4 Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 8 Terminal Capacity 9 Terminal	Contact Gap Minimum	None	
Terminal Capacity 3 Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Tax 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature Ambient Operating Temperature Fecommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 4 Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 6 Terminal Capacity 7 Terminal Capacity 8 Terminal Capacity 9 Terminal Capacity	Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 5 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Terminal Capacity 4	1 x 4mm2 Multi-strand	
Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature Recommended Location Internal Use Only Maximum Installation Altitude Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. I x 6mm2 Author Must be earthed 1 x 6mm2 Must be earthed 2 x 4mm2 Multi-strand 1 x 6mm2 Must be earthed 2 to 40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 4 Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval Patents and Trademarks All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 5 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Earth Terminal Capacity 3	3 x 2.5mm2	
Product Class 1 Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Earth Terminal Capacity 5	1 x 6mm2	
Recommended Location Internal Use Only Maximum Installation Altitude 2000m Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. Internal Use Only Maximum Installation Altitude 2000m Internal Use Only It is the policy of the company to improve products as part of our development programme.	Product Class 1	Must be earthed	
Maximum Installation Altitude Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Ambient Operating Temperature	-5° to +40°C	
Cable Outlet Minimum/Maximum Min = 0.75mm² Max = 2.5mm² Standard/Approval BS 1363-4 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Recommended Location	Internal Use Only	
Standard/Approval Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS 1363-4 Cheriton is a Registered Trade Mark No. 2344779 It is the policy of the company to improve products BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme.	Maximum Installation Altitude	2000m	
Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. It is the policy of the company to improve products as part of our development programme.	Cable Outlet Minimum/Maximum	Min = 0.75mm ² Max = 2.5mm ²	
All products listed conform to current British or European standard and the product information is All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System. BS EN ISO 9001 : 2015 Quality Management System.	Standard/Approval	BS 1363-4	
European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme.	Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779	
correct at the time of going to press. I herefore, we reserve the right to after designs and dimensions without prior notice.			as part of our development programme. Therefore, we reserve the right to alter designs
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. Correct as at 12 October 2018 04 guarantee an exact colour match and shadings of of certain finishes.	the limitations of reproduction and printing	guarantee an exact colour match and shadings of	Correct as at 12 October 2018 04:40 PM E&OE

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio