SL

## making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 90T22


Cheriton Georgian Polished Brass 2 gang 20AX 2 Way Toggle Polished Brass

Item Image

## Wiring



## Dimensions



|   |   | Bananana Banana |
|---|---|---|
| Primary Range   | Cheriton  |   |
| Insert Type   | 2 gang 20AX 2 Way Toggle  |   |
| Plate Finish  | Cheriton Georgian Box Polished Brass  |   |
| Insert Colour   | Polished Brass  |   |
| EAN13 Barcode   | 5028690352860   |   |
| Dimensions (Nominal)  | Single: Height = 88.0mm Width = 88.0mm Depth = 10.5mm   |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A   |   |
| Minimum Wall Box Depth  | 25mm  |   |
| Switched Poles  | Single  |   |
| Current Rating  | 20AX  |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 20 Amp inductive  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 5 x 1mm2  |   |
| Terminal Capacity 2   | 4 x 1.5mm2  |   |
| Terminal Capacity 3   | 2 x 2.5mm2  |   |
| Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |   |
| Terminal Capacity 5   | 1 x 6mm2  |   |
| Earth Terminal Capacity 1   | 6 x 1mm2  |   |
| Earth Terminal Capacity 2   | 5 x 1.5mm2  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |   |
| Earth Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm2  |   |
| Product Class 1   | Must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Standard/Approval   | BS EN 60669-1   |   |
| Patents and Trademarks  | Cheriton is a Registered Trade Mark No. 2344779   |   |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.  |
| Illustrations and diagrams are reproduced within  | Due to manufacturing processes we cannot  | Correct as at 12 October 2018 04:41 PM  |

guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











the limitations of reproduction and printing process and are not binding.