

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

911X60

Cheriton Georgian Antique Brass 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Antique Brass

Item Image Wiring **Dimensions** Hamilton CHERITON GEORGIAN 1X60 Primary Range Cheriton Insert Type 1 gang 600W Resistive Leading Edge Push On-Off Rotary 2 Way Switching Dimmer Plate Finish Cheriton Georgian Box Antique Brass Insert Colour Antique Brass EAN13 Barcode 5017503369454 Dimensions (Nominal) Single: Height = 88.0mm Width = 88.0mm Depth = 10.5mm Box Fixing = 60.3mm Grid Fixing = N/A Fixing Hole Centres Minimum Wall Box Depth 35mm Wattage 600W Switched Poles Single Current Rating 2.5 Amp 220/250V AC Voltage Maximum Load 600W resistive Min Load 100W Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum N/A Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Face plate must be earthed -5° to +40°C **Ambient Operating Temperature** Internal Use Only Recommended Location Maximum Installation Altitude 2000m BS EN 60669-2-1 Standard/Approval Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltage halogen lamps- dimmers Additional Notes should be de-rated by 25%. When dimming LED lamps de-rated by 75% - please contact our Technical for compatibility. Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. All products listed conform to current British or It is the policy of the company to improve products European standard and the product information is correct at the time of going to press. as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing Due to manufacturing processes we cannot guarantee an exact colour match and shadings of Correct as at 12 October 2018 04:41 PM E&OE process and are not binding. of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84















Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio