



## 91TCMB

### Cheriton Georgian Antique Brass 1 gang Telephone Master Black

| Item Image  | Wiring   | Dimensions  |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
|---|--|---|--------------------|---------------|---|---------------|--|---|--|---------------|---|--|--------------|---|--|----------------|---|--|----------------|---|--|--------------|--|--|---------------|---|
|    | <table border="1" data-bbox="662 472 964 604"> <thead> <tr> <th>Pin No.</th> <th>BT Wiring Schedule</th> <th>Colour Codes:</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Striped Wires</td> <td></td> </tr> <tr> <td>2</td> <td></td> <td>GREEN / White</td> </tr> <tr> <td>3</td> <td></td> <td>BLUE / White</td> </tr> <tr> <td>4</td> <td></td> <td>ORANGE / White</td> </tr> <tr> <td>5</td> <td></td> <td>WHITE / Orange</td> </tr> <tr> <td>6</td> <td></td> <td>WHITE / Blue</td> </tr> <tr> <td></td> <td></td> <td>WHITE / Green</td> </tr> </tbody> </table> <p data-bbox="673 604 953 661">Main Wire Colour shown in CAPITALS</p> <p data-bbox="711 613 915 661">Incoming Telephone Cable<br/>On 4 wire systems, Pin 1 and 6<br/>are not connected.</p> <p data-bbox="662 688 964 766">The maximum REN that can be connected to any one exchange line is 4. Any number of sockets may be connected. All sockets are connected in parallel, ie Pin 1 to Pin 1 ; Pin 2 to Pin 2 ; etc. as shown in the diagram above.</p> | Pin No.   | BT Wiring Schedule | Colour Codes: | 1 | Striped Wires |  | 2 |  | GREEN / White | 3 |  | BLUE / White | 4 |  | ORANGE / White | 5 |  | WHITE / Orange | 6 |  | WHITE / Blue |  |  | WHITE / Green |  <p data-bbox="1230 457 1398 527"><b>Hamilton®</b><br/>CHERITON GEORGIAN<br/>TCM<br/>Telephone Master Socket</p> |
| Pin No.   | BT Wiring Schedule   | Colour Codes:   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| 1   | Striped Wires  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| 2   |  | GREEN / White   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| 3   |  | BLUE / White  |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| 4   |  | ORANGE / White  |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| 5   |  | WHITE / Orange  |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| 6   |  | WHITE / Blue  |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
|   |  | WHITE / Green   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Primary Range   | Cheriton   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Insert Type   | 1 gang Telephone Master  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Plate Finish  | Cheriton Georgian Box Antique Brass  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Insert Colour   | Black  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| EAN13 Barcode   | 5017503361649  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Dimensions (Nominal)  | Single: Height = 88.0mm Width = 88.0mm Depth = 10.5mm  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Minimum Wall Box Depth  | 25mm   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Switched Poles  | N/A  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| IP Rating   | IP2XD  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Contact Gap Minimum   | N/A  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup> Multi-strand  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Product Class 1   | Must be earthed (ref BS7671 415.2.1)   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Recommended Location  | Internal Use Only  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Maximum Installation Altitude   | 2000m  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Patents and Trademarks  | Cheriton is a Registered Trade Mark No. 2344779  |   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 12 October 2018 04:41 PM E&OE   |                    |               |   |               |  |   |  |               |   |  |              |   |  |                |   |  |                |   |  |              |  |  |               |   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
T: +44 (0)1747 860088 F: +44 (0)1179 710414  
E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
Registered in London No. 941624 VAT Registration No. 222 6607 84

