## Hamilton

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio 922XLEDITB100 Cheriton Victorian Polished Brass 2g 100W LED 2 Way Push On/Off Rotary Dimmer Polished Brass Item Image Wiring Dimensions Hemilton CHERITON VICTORIAN 2XLEDITB LEDITB100 2 Way Dimmer Primary Range Cheriton Insert Type 2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Cheriton Victorian Box Polished Brass Insert Colour Polished Brass EAN13 Barcode 5017504081768 Dimensions (Nominal) Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD **Terminal Capacity 1** 2X1mm<sup>2</sup> **Terminal Capacity 2** 2X1.5mm<sup>2</sup> Earth Terminal Capacity 1 5X1mm<sup>2</sup> Earth Terminal Capacity 2 4X1.5mm<sup>2</sup> Earth Terminal Capacity 3 3X2.5mm<sup>2</sup> Earth Terminal Capacity 4 1X4mm<sup>2</sup> Multi-Strand Earth Terminal Capacity 5 1X6mm<sup>2</sup> Product Class 1 Face plate muct be earthed -5°C to +40°C Ambient Operating Temperature **Recommended Location** Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS EN 60669-2-1 Additional Notes Trailing Edge & Leading Edge Dimmer Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779 All products listed conform to current British or All accessories are manufactured under an accredited It is the policy of the company to improve products European standard and the product information is BS EN ISO 9001 : 2015 Quality Management System. as part of our development programme Therefore, we reserve the right to alter designs correct at the time of going to press. and dimensions without prior notice. Illustrations and diagrams are reproduced within Due to manufacturing processes we cannot Correct as at 12 October 2018 04:41 PM the limitations of reproduction and printing guarantee an exact colour match and shadings of E&OE process and are not binding. of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Listed in STrimble T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.bossilte...!! SECA Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84 hamilton-litestat.com www.hamilton-litestat.com

922XLEDITB100 - Cheriton Victorian Polished Brass 2g 100W LED 2 Way Push On/Off Rotary Dimmer Polished Brass

SL