




## 92DPNCPB-W

Cheriton Victorian Polished Brass 1 gang 20AX Double Pole Rocker and Neon and Cable Outlet Polished Brass/White

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|  |  |  |

|                               |  |
|-------------------------------|--|
| Primary Range                 | Cheriton   |
| Insert Type                   | 1 gang 20AX Double Pole Rocker + Neon + Cable Outlet |
| Plate Finish                  | Cheriton Victorian Box Polished Brass                |
| Insert Colour                 | Polished Brass/White                                 |
| EAN13 Barcode                 | 5017503373857  |
| Dimensions (Nominal)          | Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm |
| Fixing Hole Centres           | Box Fixing = 60.3mm Grid Fixing = N/A                |
| Minimum Wall Box Depth        | 25mm   |
| Switched Poles                | Double   |
| Current Rating                | 20AX   |
| Voltage                       | 220/250V AC  |
| Maximum Load                  | 20 Amp inductive                                     |
| Mains Frequency               | 50Hz   |
| IP Rating                     | IP2XD  |
| Contact Gap Minimum           | 3mm  |
| Terminal Capacity 1           | 3 x 2.5mm <sup>2</sup>                               |
| Terminal Capacity 2           | 2 x 4mm <sup>2</sup> Multi Strand                    |
| Terminal Capacity 3           | 1 x 6mm <sup>2</sup>                                 |
| Earth Terminal Capacity 1     | 6 x 1mm <sup>2</sup>                                 |
| Earth Terminal Capacity 2     | 5 x 1.5mm <sup>2</sup>                               |
| Earth Terminal Capacity 3     | 3 x 2.5mm <sup>2</sup>                               |
| Earth Terminal Capacity 4     | 2 x 4mm <sup>2</sup> Multi-strand                    |
| Earth Terminal Capacity 5     | 1 x 6mm <sup>2</sup>                                 |
| Product Class 1               | Must be earthed                                      |
| Ambient Operating Temperature | -5° to +40°C   |
| Recommended Location          | Internal Use Only                                    |
| Maximum Installation Altitude | 2000m  |
| Cable Outlet Minimum/Maximum  | Min = 0.75mm <sup>2</sup> Max = 2.5mm <sup>2</sup>   |
| Standard/Approval             | BS EN 60669-1  |
| Patents and Trademarks        | Cheriton is a Registered Trade Mark No. 2344779      |

|  |  |  |
|--|--|--|
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>         | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>                | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p> | <p>Correct as at 12 October 2018 04:41 PM E&amp;OE</p>   |