Product Class 1

Ambient Operating Temperature

Maximum Installation Altitude

Recommended Location

Patents and Trademarks

Standard/Approval

Item Image



making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

92R22PB-W

Cheriton Victorian Polished Brass 2 gang 10AX 2 Way Rocker Polished Brass/White

Wiring

Hamilton Primary Range Cheriton Insert Type 2 gang 10AX 2 Way Rocker Plate Finish Cheriton Victorian Box Polished Brass Insert Colour Polished Brass/White EAN13 Barcode 5017503373222 Dimensions (Nominal) Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm Weight 173 GR Fixing Hole Centres Box Fixing = 60.3mm Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single Current Rating 10AX 220/250V AC Voltage Maximum Load 10 Amp inductive 50Hz Mains Frequency IP Rating IP2XD Contact Gap Minimum 3mm Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 1 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of the limitations of reproduction and printing process and are not binding. of certain finishes R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

All products listed conform to current British or European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

Must be earthed

Internal Use Only

BS EN 60669-1

Cheriton is a Registered Trade Mark No. 2344779

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

-5° to +40°C

2000m







It is the policy of the company to improve products as part of our development programme.

Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 12 October 2018 04:42 PM







Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio