SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

92RRTPB-B

Cheriton Victorian Polished	<u>92RRTPB-B</u> Brass 1 gang 10AX Push To Make Retractive	e Rocker Polished Brass/Black	
Item Image	Wiring	Dimensions	
	Com L2 L1	Hemiton CHERITON VICTORIAN RRT Push to Make Retractive Rocker	
Primary Range	Cheriton		
Insert Type	1 gang 10AX Push To Make Retractive Rocker		
Plate Finish	Cheriton Victorian Box Polished Brass		
Insert Colour	Polished Brass/Black		
EAN13 Barcode	5017503372195		
Dimensions (Nominal)	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A		
Minimum Wall Box Depth	25mm		
Switched Poles	Single		
Current Rating	10AX		
Voltage	220/250V AC		
Maximum Load	10 Amp inductive		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	3mm		
Terminal Capacity 1	5 x 1mm2		
	4 x 1.5mm2		
Terminal Capacity 2	1 x 2.5mm2		
Terminal Capacity 3			
Terminal Capacity 4	1 x 4mm2 Multi-strand		
Terminal Capacity 5	1 x 6mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-1		
Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 12 October 2018 04:42 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

of certain finishes.









