




## 93SPNCBL-B

Cheriton Victorian Antique Brass 1 gang 13A Double Pole Fused Spur and Neon and Cable Outlet Black/Black

| Item Image  | Wiring  | Dimensions  |
|---|---|---|
|    |                              |    |
| Primary Range   | Cheriton  |   |
| Insert Type   | 1 gang 13A Double Pole Fused Spur + Neon + Cable Outlet   |   |
| Plate Finish  | Cheriton Victorian Box Antique Brass  |   |
| Insert Colour   | Black/Black   |   |
| EAN13 Barcode   | 5017504088767   |   |
| Dimensions (Nominal)  | Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm  |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A   |   |
| Minimum Wall Box Depth  | 35mm  |   |
| Switched Poles  | Double  |   |
| Current Rating  | 13 Amp  |   |
| Voltage   | 220/250V AC   |   |
| Maximum Load  | 13 Amp  |   |
| Mains Frequency   | 50Hz  |   |
| IP Rating   | IP2XD   |   |
| Contact Gap Minimum   | 3mm   |   |
| Terminal Capacity 1   | 3 x 2.5mm <sup>2</sup>  |   |
| Terminal Capacity 2   | 2 x 4mm <sup>2</sup> Multi Strand   |   |
| Terminal Capacity 3   | 1 x 6mm <sup>2</sup>  |   |
| Earth Terminal Capacity 1   | 6 x 1mm <sup>2</sup>  |   |
| Earth Terminal Capacity 2   | 5 x 1.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 3   | 3 x 2.5mm <sup>2</sup>  |   |
| Earth Terminal Capacity 4   | 2 x 4mm <sup>2</sup> Multi-strand   |   |
| Earth Terminal Capacity 5   | 1 x 6mm <sup>2</sup>  |   |
| Product Class 1   | Must be earthed   |   |
| Ambient Operating Temperature   | -5° to +40°C  |   |
| Recommended Location  | Internal Use Only   |   |
| Maximum Installation Altitude   | 2000m   |   |
| Cable Outlet Minimum/Maximum  | Min = 0.75mm <sup>2</sup> Max = 2.5mm <sup>2</sup>  |   |
| Standard/Approval   | BS 1363-4   |   |
| Additional Notes  | Cable Outlets Fitted with Clamps: Yes   |   |
| Patents and Trademarks  | Cheriton is a Registered Trade Mark No. 2344779   |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.         | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 12 October 2018 04:42 PM E&OE   |