Hamilton

making connections beautifully

	Wiring Accessories • Circuit Protection • Sn	nart Lighting Control & Multi-room Audio
	<u>93T21</u>	
Cheriton Victorian Antique Brass 1 gang 20AX 2 Way Toggle Antique Brass		
Chemon victorian Antique Diass i gang 20AX 2 way roggie Antique Diass		
Item Image	Wiring	Dimensions
1 1 3		Hemilton cheriton Victorian 121 2 Way Toggle
€ •	Abende 2 wy webzig	
Primary Range	Cheriton	
Insert Type	1 gang 20AX 2 Way Toggle	
Plate Finish	Cheriton Victorian Box Antique Brass	
Insert Colour	Antique Brass	
EAN13 Barcode	5028690382850	
Dimensions (Nominal)	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A	
Minimum Wall Box Depth	25mm	
Switched Poles	Single	
Current Rating	20AX	
	220/250V AC	
Voltage		
Maximum Load	20 Amp inductive	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	3mm	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-strand	
Terminal Capacity 5	1 x 6mm2	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Standard/Approval	BS EN 60669-1	
Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 12 October 2018 04:42 PN E&Ol
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Re T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O E: info@hamilton-litestat.com Registered in	bad, Brislington, Bristol, BS4 5NZ ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Trimble Product Product CEX No. 1941

SL