Hamilton

making connections beautifully

| | <u>93T23</u> | |
|---|---|--|
| | | |
| Cheriton Victo | rian Antique Brass 3 gang 20AX 2 Way Toggle | e Antique Brass |
| Item Image | Wiring | Dimensions |
| → (a) → (b) → (c) <li< th=""><th rowspan="2">Image: state stat</th><th>Hemilton CHERITON VICTORIAN T23 2 Way Toggle</th></li<> | Image: state stat | Hemilton CHERITON VICTORIAN T23 2 Way Toggle |
| | | |
| Primary Range | Cheriton | |
| Insert Type | 3 gang 20AX 2 Way Toggle | |
| Plate Finish | Cheriton Victorian Box Antique Brass | |
| Insert Colour | Antique Brass | |
| EAN13 Barcode | 5028690382874 | |
| Dimensions (Nominal) | Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 25mm | |
| Switched Poles | Single | |
| | 20AX | |
| Current Rating | 220/250V AC | |
| Voltage | | |
| Maximum Load | 20 Amp inductive | |
| Mains Frequency | 50Hz | |
| IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 5 x 1mm2 | |
| Terminal Capacity 2 | 4 x 1.5mm2 | |
| Terminal Capacity 3 | 2 x 2.5mm2 | |
| Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Terminal Capacity 5 | 1 x 6mm2 | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Standard/Approval | BS EN 60669-1 | |
| Patents and Trademarks | Cheriton is a Registered Trade Mark No. 2344779 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 12 October 2018 04:42 PI E&O |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville F T: +44 (0)1747 860088 F: +44 (0)179 710414 Registered E: info@hamilton-litestat.com www.hamilton-litestat.com Registered | Orad, Brislington, Bristol, BS4 5NZ Office 1 Rushmills, Bedford Road, Northampton NN4 7YB n London No. 941624 VAT Registration No. 222 6607 84 | Listed in Primitic product product Selector CRI. No. 101128 |

SL