SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## 941XTSSB-W

Cheriton Victorian Satin Brass 1 gang Multi-Way Touch Slave Controller Satin Brass/White

Wiring

Item Image

## Multi-Way Wiring using Stave module(s)



Primary Range	Cheriton		
Insert Type	1 gang Multi-Way Touch Slave Controller		
Plate Finish	Cheriton Victorian GRID-IT Satin Brass		
Insert Colour	Satin Brass/White		
EAN13 Barcode	5028690390428	5028690390428	
Dimensions (Nominal)	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm	
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = 49.2mm		
Minimum Wall Box Depth	35mm	35mm	
Wattage	The same as Touch Master or Ceiling Dimmer		
Switched Poles	N/A		
Current Rating	The same as Touch Master or Ceiling Dimmer	The same as Touch Master or Ceiling Dimmer	
Voltage	220/250V AC		
Maximum Load	The same as Touch Master		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Contact Gap Minimum	N/A		
Terminal Capacity 1	2 x 1mm2		
Terminal Capacity 2	2 x 1.5mm2		
Earth Terminal Capacity 1	5 x 1mm2		
Earth Terminal Capacity 2	4 x 1.5mm2		
Earth Terminal Capacity 3	3 x 2.5mm2		
Earth Terminal Capacity 4	1 x 4mm2 Multi-strand		
Earth Terminal Capacity 5	1 x 6mm2		
Product Class 1	Face plate must be earthed		
Ambient Operating Temperature	-5° to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Tungsten filament GU10 lamps must be branded with a fuse base. When using mains voltagehalogen lamps- dimmers should be de-rated by 25%. When using mains voltage halogen load transformer - maximum rating is 210VA. To only be used with Touch Master Dimmers		
Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779		
All products listed conform to current British or European standard and the product information is	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  It is the policy of the company to i as part of our development; Therefore, we request to girly	programme.	

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)17179 710414 Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB

E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in London No. 941624 VAT Registration No. 222 6607 84







as part of our development programme.

Therefore, we reserve the right to alter designs and dimensions without prior notice.



Correct as at 12 October 2018 04:43 PM



European standard and the product information is correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.





Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio