SL

## making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## 9445SS1SB-W

Cheriton Victorian Satin Brass 45A Double Pole Rocker + Neon + 13A Switched Socket Red+Satin Brass/White

Item Image









European standard and the product information is  Correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  as part of our development programme.  Therefore, we reserve the right to alter design			
Plate Finish Cheriton Victorian Box Satin Brass Insert Colour Red+Satin Brass/White  EAN13 Barcode 5017503393701 Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm  Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency 50Hz IP Rating IPZXD Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° t 40°C Maximum Installation Altitude 2000m Slandard/Approval BS 4177 Patents and Trademarks Cherikons and Fisch Converse were replant and reproduct information is Correct at the time of gloing to press.  All product listed conform to current British or European standard and the product information is Correct at the time of gloing to press.	Primary Range	Cheriton	
Insert Colour Red+Satin Brass/White  EAN13 Barcode 5017503393701  Dimensions (Nominal) Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm  Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A  Minimum Wall Box Depth 35mm  Switched Poles Double  Current Rating Switch 45 Amp Socket 13 Amp  Voltage 220/250V AC  Maximum Load Switch 45 Amp Socket 13 Mm  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 6mm2  Terminal Capacity 2 2 x 10mm2  Terminal Capacity 3 1 x 16mm2  Earth Terminal Capacity 1 3 x 6mm2  Earth Terminal Capacity 2 2 x 10mm2  Earth Terminal Capacity 3 1 x 16mm2  Earth Terminal	Insert Type	45A Double Pole Red Rocker + Neon + 13A Switched Socket	
EAN13 Barcode 5017503393701  Dimensions (Nominal) Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm  Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A  Minimum Wall Box Depth 35mm  Switched Poles Double  Current Rating Switch 45 Amp Socket 13 Amp  Voltage 220/250V AC  Maximum Load Switch 45 Amp Socket 13  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 6mm2  Terminal Capacity 2 2 x 10mm2  Earth Terminal Capacity 1 3 x 6mm2  Earth Terminal Capacity 1 3 x 6mm2  Earth Terminal Capacity 2 2 x 10mm2  Earth Terminal Capacity 3 1 x 16mm2  Earth Terminal Capacity 1 x 16mm2  Earth Terminal Capacity 1 x 16mm2  Earth Terminal C	Plate Finish	Cheriton Victorian Box Satin Brass	
Dimensions (Nominal) Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Switched Poles Double Current Rating Switch 45 Amp Socket 13 Amp Voltage 220/250V AC Maximum Load Switch 45 Amp Socket 13 Mains Frequency Fixing Fixing IP2XD Contact Cap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 3 1 x 16mm2 Farth Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity	Insert Colour	Red+Satin Brass/White	
Fixing Hole Centres  Box Fixing = 120.6mm Grid Fixing = N/A  Minimum Wall Box Depth  35mm  Switch de Poles  Current Rating  Switch 45 Amp Socket 13 Amp  Voltage  220/250V AC  Maximum Load  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  3mm  3reminal Capacity 1  3 x 6mm2  Terminal Capacity 2  2 x 10mm2  Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 3  1 x 16mm2  Forduct Class 1  Must be earthed  Ambient Operating Temperature  3° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  All products listed conform to current British or European standard and the product information is correct at the time of oging to press.  All products listed conform to current British or European standard and the product information is correct at the time of oging to press.	EAN13 Barcode	5017503393701	
Minimum Wall Box Depth  Switched Poles  Double  Current Rating  Switch 45 Amp Socket 13 Amp  Voltage  220/250V AC  Maximum Load  Mains Frequency  SoHz  IP Rating  IP2XD  Contact Gap Minimum  3 mm  Terminal Capacity 1  3 x 6mm2  Terminal Capacity 2  2 x 10mm2  Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 1  3 x 6 mm2  Earth Terminal Capacity 2  2 x 10mm2  Earth Terminal Capacity 3  1 x 16mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  All products listed conform to current British or European standard and the product information is correct at the time of oging to press.  All products listed conform to current British or European standard and the product information is correct at the time of oging to press.	Dimensions (Nominal)	Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm	
Switched Poles  Double  Current Rating  Switch 45 Amp Socket 13 Amp  Voltage  220/250V AC  Maximum Load  Switch 45 Amp Socket 13  Mains Frequency  1P Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  3 x 6mm2  Terminal Capacity 2  2 x 10mm2  Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 2  2 x 10mm2  Farth Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 3  1 x 16mm2  Foduct Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design and rook appared to represent the right to alter design and rook appared to represent the right to alter design and rook appared to represent the right to alter design and rook appared to represent the right to alter design and rook appared to represent the right to alter design and rook appared to represent the right to alter design and rook appared to represent the refers the right to alter design and rook appared to represent the refers to alter design and rook appared to represent the refers to alter design and rook appared to represent the refers the refers the refers and refers the refers	Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A	
Current Rating Switch 45 Amp Socket 13 Amp  Voltage 220/250V AC  Maximum Load Switch 45 Amp Socket 13  Mains Frequency 50Hz  IP Rating IP2XD  Contact Gap Minimum 3mm  Terminal Capacity 1 3 x 6mm2  Terminal Capacity 2 2 x 10mm2  Terminal Capacity 3 1 x 16mm2  Earth Terminal Capacity 1 3 x 6mm2  Earth Terminal Capacity 1 1 x 16mm2  Earth Terminal Capacity 3 1 x 16mm2  Forduct Class 1 Must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 4177  All products listed conform to current British or European standard and the product information is correct at the time of gloing to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  Therefore, we reserve the right to later design the reserved to the server to right to later design the reserved to the reserved to the company to improve processing the reserved to the company to improve processing the reserved to	Minimum Wall Box Depth	35mm	
Voltage   220/250V AC	Switched Poles	Double	
Maximum Load  Switch 45 Amp Socket 13  Mains Frequency  50Hz  IP Rating  IP2XD  Contact Gap Minimum  3mm  Terminal Capacity 1  3 x 6mm2  Terminal Capacity 2  2 x 10mm2  Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 1  2 x 10mm2  Earth Terminal Capacity 2  2 x 10mm2  Earth Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 3  1 x 16mm2  Froduct Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Maximum Installation Altitude  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of gloing to press.  All accessories are manufactured under an accredited BS EN ISO 9001: 2015 Quality Management System.  It is the policy of the company to improve produce as part of our development programmen.  Therefore, we reserve the right to alter designation and the reduction of the red	Current Rating	Switch 45 Amp Socket 13 Amp	
Mains Frequency    Pating   IP2XD	Voltage	220/250V AC	
IP Rating Contact Gap Minimum 3mm Terminal Capacity 1 3 x 6mm2 Terminal Capacity 2 2 x 10mm2 Terminal Capacity 3 1 x 16mm2 Earth Terminal Capacity 1 2 x 10mm2 Earth Terminal Capacity 1 3 x 6mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 2 2 x 10mm2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Recommended Location Internal Use Only Maximum Installation Altitude 2000m Standard/Approval BS 4177 Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to altered exist of our development programme. Therefore, we reserve the right to altered exist of the company to improve programme. Therefore, we reserve the right to altered exist of the company to improve programme. Therefore, we reserve the right to altered exist of the company to improve programme. Therefore, we reserve the right to altered exist of the company to improve programme. Therefore, we reserve the right to altered exist of the company to improve programme. Therefore, we reserve the right to altered exist of the company to improve programme.	Maximum Load	Switch 45 Amp Socket 13	
Contact Gap Minimum  3mm  Terminal Capacity 1  3 x 6mm2  Terminal Capacity 2  2 x 10mm2  Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 2  2 x 10mm2  Earth Terminal Capacity 2  2 x 10mm2  Earth Terminal Capacity 3  1 x 16mm2  Product Class 1  Ambient Operating Temperature  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to atter design to later design the refore, we reserve the right to atter design the refore, we reserve the right to atter design the refore the right to atter design the reforement of the refore, we reserve the right to atter design the reforement of the refore, we reserve the right to atter design the reforement of the refore, we reserve the right to atter design the reforement of the refore, we reserve the right to atter design the reforement of	Mains Frequency	50Hz	
Terminal Capacity 1 3 x 6mm2  Terminal Capacity 2 2 x 10mm2  Terminal Capacity 3 1 x 16mm2  Earth Terminal Capacity 1 3 x 6mm2  Earth Terminal Capacity 2 2 x 10mm2  Earth Terminal Capacity 2 1 x 16mm2  Earth Terminal Capacity 3 1 x 16mm2  Product Class 1 Must be earthed  Ambient Operating Temperature 5° to +40°C  Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 4177  Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter design to the reserve the right to alter the time of going to press.	IP Rating	IP2XD	
Terminal Capacity 2  2 x 10mm2  Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 1  3 x 6mm2  Earth Terminal Capacity 2  2 x 10mm2  Earth Terminal Capacity 2  2 x 10mm2  Earth Terminal Capacity 3  1 x 16mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design	Contact Gap Minimum	3mm	
Terminal Capacity 3  Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 2  Earth Terminal Capacity 3  1 x 16mm2  Earth Terminal Capacity 3  1 x 16mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to a part of our development programmen. Therefore, we reserve the right to alter design to a part of our development programmen. Therefore, we reserve the right to alter design to a part of our development programmen. Therefore, we reserve the right to alter design to a part of our development programmen. Therefore, we reserve the right to alter design to a part of our development programmen.	Terminal Capacity 1	3 x 6mm2	
Earth Terminal Capacity 1  Earth Terminal Capacity 2  Earth Terminal Capacity 3  Earth Terminal Capacity 3  I x 16mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to alter the sign to alter design.	Terminal Capacity 2	2 x 10mm2	
Earth Terminal Capacity 2  Earth Terminal Capacity 3  1 x 16mm2  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to alter the sight to alter design.	Terminal Capacity 3	1 x 16mm2	
Earth Terminal Capacity 3  Product Class 1  Must be earthed  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to alter the sight to alter design.	Earth Terminal Capacity 1	3 x 6mm2	
Product Class 1  Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to alter the sign than alter the sign	Earth Terminal Capacity 2	2 x 10mm2	
Ambient Operating Temperature  -5° to +40°C  Recommended Location  Internal Use Only  Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to a superior to the reserve the right to alter design to a superior to the reserve the right to alter design to a superior to	Earth Terminal Capacity 3	1 x 16mm2	
Recommended Location Internal Use Only  Maximum Installation Altitude 2000m  Standard/Approval BS 4177  Patents and Trademarks Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to a spart of our development programme.  Therefore, we reserve the right to alter design to a spart of our development programme.	Product Class 1	Must be earthed	
Maximum Installation Altitude  2000m  Standard/Approval  BS 4177  Patents and Trademarks  Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design to alter design to alter the sign to alter design to alter the sign than the	Ambient Operating Temperature	-5° to +40°C	
Standard/Approval  Patents and Trademarks  Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter design.	Recommended Location	Internal Use Only	
Patents and Trademarks  Cheriton is a Registered Trade Mark No. 2344779  All products listed conform to current British or European standard and the product information is correct at the time of going to press.  Cheriton is a Registered Trade Mark No. 2344779  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. Therefore, we reserve the right to alter designation of the company to improve proving as part of our development programme. Therefore, we reserve the right to alter designation of the company to improve proving as part of our development programme.	Maximum Installation Altitude	2000m	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.  All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  Therefore, we reserve the right to alter designation of the company to improve processing the conformation is as part of our development programme.  Therefore, we reserve the right to alter designation of the company to improve processing the company the company to improve processing the company to improve	Standard/Approval	BS 4177	
European standard and the product information is correct at the time of going to press.  BS EN ISO 9001 : 2015 Quality Management System.  as part of our development programme. Therefore, we reserve the right to alter design	Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779	
and dimensions without prior notice.	European standard and the product information is		It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











Correct as at 12 October 2018 04:43 PM



E&OE