SL

making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


9445VW

Cheriton Victorian Satin Brass 1 gang 45A Double Pole Rocker and Neon (Vertically Mounted) Red/White

Wiring

Item Image





Dimensions

| 6 | | | |
|---|---|--|--|
| Primary Range | Cheriton | | |
| Insert Type | 1 gang 45A Double Pole Red Rocker + Neon (Vertically Mounted) | | |
| Plate Finish | Cheriton Victorian Box Vertical Satin Brass | | |
| Insert Colour | Red/White | Red/White | |
| EAN13 Barcode | 5017503394999 | | |
| Dimensions (Nominal) | Double: Height = 146.0mm Width = 86.5mm Depth = 7.5mm | | |
| Fixing Hole Centres | Box Fixing = 120.6mm Grid Fixing = N/A | | |
| Minimum Wall Box Depth | 35mm | | |
| Switched Poles | Double | | |
| Current Rating | 45 Amp | | |
| Voltage | 220/250V AC | | |
| Maximum Load | 45 Amp | | |
| Mains Frequency | 50Hz | | |
| IP Rating | IP2XD | | |
| Contact Gap Minimum | 3mm | | |
| Terminal Capacity 1 | 3 x 6mm2 | | |
| Terminal Capacity 2 | 2 x 10mm2 | | |
| Terminal Capacity 3 | 1 x 16mm2 | | |
| Earth Terminal Capacity 1 | 3 x 6mm2 | | |
| Earth Terminal Capacity 2 | 2 x 10mm2 | | |
| Earth Terminal Capacity 3 | 1 x 16mm2 | | |
| Product Class 1 | Must be earthed | | |
| Ambient Operating Temperature | -5° to +40°C | | |
| Recommended Location | Internal Use Only | | |
| Maximum Installation Altitude | 2000m | | |
| Standard/Approval | BS EN 60669-1 | | |
| Additional Notes | Must be mounted vertically | | |
| Patents and Trademarks | Cheriton is a Registered Trade Mark No. 2344779 | | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. | |
| 1 | | 1 | |

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

Illustrations and diagrams are reproduced within the limitations of reproduction and printing

process and are not binding.

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











Correct as at 12 October 2018 04:43 PM

