SL

Item Image

making connections beautifully

Dimensions

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

944XLEDITB100

Cheriton Victorian Satin Brass 4g 100W LED 2 Way Push On/Off Rotary Dimmer Satin Brass

Wiring

Hamilton CHERITON VICTORIAN
4XLEDITB
LEDITB100 2 Way Dimmer Primary Range Cheriton Insert Type 4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer Plate Finish Cheriton Victorian Box Satin Brass Insert Colour Satin Brass EAN13 Barcode 5017504081867 Dimensions (Nominal) Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm Fixing Hole Centres Box Fixing = 120.6mm Grid Fixing = N/A Minimum Wall Box Depth 35mm Wattage 5-70W Per Gang Switched Poles Single Current Rating 0.3A Per Gang Voltage 230V-240V Maximum Load 5-70W Per Gang Mains Frequency 50Hz IP Rating IP2XD Terminal Capacity 1 2X1mm² Terminal Capacity 2 2X1.5mm² Earth Terminal Capacity 1 5X1mm² Earth Terminal Capacity 2 4X1.5mm² Earth Terminal Capacity 3 3X2.5mm² Earth Terminal Capacity 4 1X4mm² Multi-Strand Earth Terminal Capacity 5 1X6mm² Product Class 1 Face plate muct be earthed

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within

the limitations of reproduction and printing

process and are not binding.

Ambient Operating Temperature Recommended Location

Maximum Installation Altitude

Patents and Trademarks

Standard/Approval

Additional Notes

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YE Registered in London No. 941624 VAT Registration No. 222 6607 84

-5°C to +40°C

2000m

Internal Use Only

BS EN 60669-2-1

Trailing Edge & Leading Edge Dimmer

Cheriton is a Registered Trade Mark No. 2344779

All accessories are manufactured under an accredited

BS EN ISO 9001: 2015 Quality Management System.

Due to manufacturing processes we cannot

guarantee an exact colour match and shadings of







It is the policy of the company to improve products

as part of our development programme.

Therefore, we reserve the right to alter designs

and dimensions without prior notice.



Correct as at 12 October 2018 04:43 PM



E&OE