SL

making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

951XLEDITB100

Cheriton Victorian Bright Chrome 1g 100W LED 2 Way Push On/Off Rotary Dimmer Bright Chrome

Item Image

Wiring

Dimensions



	95.5 O
Primary Range	Cheriton
Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dim
Plate Finish	Cheriton Victorian Box Bright Chrome
Insert Colour	Bright Chrome
EAN13 Barcode	5017504081874
Dimensions (Nominal)	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A
Minimum Wall Box Depth	35mm
Wattage	5-100W (10 LED Lamps MAX)

Insert Type	1 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer		
Plate Finish	Cheriton Victorian Box Bright Chrome		
Insert Colour	Bright Chrome		
EAN13 Barcode	5017504081874		
Dimensions (Nominal)	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm		
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = N/A		
Minimum Wall Box Depth	35mm		
Wattage	5-100W (10 LED Lamps MAX)		
Switched Poles	Single		
Current Rating	0.4A		
Voltage	230V-240V		
Maximum Load	5-100W (10 LED Lamps MAX)		
Mains Frequency	50Hz		
IP Rating	IP2XD		
Terminal Capacity 1	2X1mm²		
Terminal Capacity 2	2X1.5mm²		
Earth Terminal Capacity 1	5X1mm²		
Earth Terminal Capacity 2	4X1.5mm²		
Earth Terminal Capacity 3	3X2.5mm²		
Earth Terminal Capacity 4	1X4mm² Multi-Strand		
Earth Terminal Capacity 5	1X6mm²		
Product Class 1	Face plate muct be earthed		
Ambient Operating Temperature	-5°C to +40°C		
Recommended Location	Internal Use Only		
Maximum Installation Altitude	2000m		
Standard/Approval	BS EN 60669-2-1		
Additional Notes	Trailing Edge & Leading Edge Dimmer		
Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779		
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of	Correct as at 12 October 2018 04:43 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84











