SL

## making connections beautifully

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio


## 95SS2BC-B

Cheriton Victorian Bright Chrome 2 gang 13A Double Pole Switched Socket Bright Chrome/Black

Item Image



Wiring



Dimensions




Plate Finish Cheriton V Insert Colour Bright Che EAN13 Barcode 50175034		mm	
Plate Finish Cheriton V Insert Colour Bright Chr EAN13 Barcode 50175034	rictorian Box Bright Chrome ome/Black 06029	mm	
Insert Colour Bright Chi EAN13 Barcode 50175034	ome/Black 06029	mm	
EAN13 Barcode 50175034	06029	mm	
		mm	
	Height = 86.5mm Width = 146.0mm Depth = 7.5r	mm	
Dimensions (Nominal) Double:		Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm	
Weight 285 GR	285 GR		
Fixing Hole Centres Box Fixing	Box Fixing = 120.6mm Grid Fixing = N/A		
Minimum Wall Box Depth 35mm	35mm		
Switched Poles Double	Double		
Current Rating 13 Amp	13 Amp		
Voltage 220/250V	220/250V AC		
Maximum Load 13 Amp	13 Amp		
Mains Frequency 50Hz	50Hz		
IP Rating IP2XD	IP2XD		
Contact Gap Minimum 3mm	3mm		
Terminal Capacity 1 4 x 2.5mn	4 x 2.5mm2		
Terminal Capacity 2 3 x 4mm2	3 x 4mm2		
Terminal Capacity 3 2 x 6mm2	2 x 6mm2 Multi-Strand		
Terminal Capacity 4 1 x 10mm	2		
Earth Terminal Capacity 1 4 x 2.5mm	4 x 2.5mm2		
Earth Terminal Capacity 2 3 x 4mm2	3 x 4mm2		
Earth Terminal Capacity 3 2 x 6mm2	2 x 6mm2 Multi-strand		
Earth Terminal Capacity 4 1 x 10mm	1 x 10mm2		
Product Class 1 Must be e	Must be earthed		
Ambient Operating Temperature -5° to +40	-5° to +40°C		
Recommended Location Internal U	Internal Use Only		
Maximum Installation Altitude 2000m	2000m		
Standard/Approval BS 1363-	BS 1363-2		
Additional Notes Dual Earth	Dual Earth: Yes		
Patents and Trademarks Cheriton i	Cheriton is a Registered Trade Mark No. 2344779		
	accessories are manufactured under an accredited EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme.  Therefore, we reserve the right to alter designs and dimensions without prior notice.	
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot uarantee an exact colour match and shadings of of certain finishes.	Correct as at 12 October 2018 04:44 PM E&OE	

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84









