## Hamilton

## making connections beautifully

|  | Wiring Accessories • Circuit Protection • Sr  |  |
|--|---|--|
|  |   | Shing concord har son Adda   |
| <u>96RRTSC-W</u>   |   |  |
| Cheriton Victorian Satin Chrome 1 gang 10AX Push To Make Retractive Rocker Satin Chrome/White  |   |  |
| Item Image   | Wiring  | Dimensions   |
|  |   |  |
| ÷  | Com<br>Com  | CHERITON VICTORIAN<br>RR<br>Push to Make Retractive Rocker   |
|  | $ \begin{array}{c} J \\ \bigcirc \\ \Box \\ \Box$                                       |  |
| Primary Range  | Cheriton  |  |
| Insert Type  | 1 gang 10AX Push To Make Retractive Rocker  |  |
| Plate Finish   | Cheriton Victorian Box Satin Chrome   |  |
| Insert Colour  | Satin Chrome/White  |  |
| EAN13 Barcode  | 5017503417193   |  |
| Dimensions (Nominal)   | Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm  |  |
| Fixing Hole Centres  | Box Fixing = 60.3mm Grid Fixing = N/A   |  |
| Minimum Wall Box Depth   | 25mm  |  |
| Switched Poles   | Single  |  |
| Current Rating   | 10AX  |  |
| Voltage  | 220/250V AC   |  |
| Maximum Load   | 10 Amp inductive  |  |
| Mains Frequency  | 50Hz  |  |
| IP Rating  | IP2XD   |  |
| Contact Gap Minimum  | 3mm   |  |
| Terminal Capacity 1  | 5 x 1mm2  |  |
| Terminal Capacity 2  | 4 x 1.5mm2  |  |
| Terminal Capacity 3  | 1 x 2.5mm2  |  |
| Terminal Capacity 4  | 1 x 4mm2 Multi-strand   |  |
| Terminal Capacity 5  | 1 x 6mm2  |  |
| Earth Terminal Capacity 1  | 5 x 1mm2  |  |
| Earth Terminal Capacity 2  | 4 x 1.5mm2  |  |
| Earth Terminal Capacity 3  | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4  | 1 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5  | 1 x 6mm2  |  |
| Product Class 1  | Must be earthed   |  |
| Ambient Operating Temperature  | -5° to +40°C  |  |
| Recommended Location   | Internal Use Only   |  |
| Maximum Installation Altitude  | 2000m   |  |
| Standard/Approval  | BS EN 60669-1   |  |
| Patents and Trademarks   | Cheriton is a Registered Trade Mark No. 2344779   |  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press.  | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.   | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.                             | Correct as at 12 October 2018 04:45 PM<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro<br>T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O<br>E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | ad, Brislington, Bristol, BS4 5NZ<br>ffice 1 Rushmills, Bedford Road, Northampton NN4 7YB<br>London No. 941624 VAT Registration No. 222 6607 84 | Listed in STrimble product selector DSSPUs (Ext. No. FM1228)   |