Hamilton

making connections beautifully

SL

| 32 | that the optimie | ctoris beautifully |
|---|--|--|
| | Wiring Accessories • Circuit Protection • Sn | nart Lighting Control & Multi-room Audio |
| <u>96SPNCBL-B</u> | | |
| Cheriton Victorian Satin Chrome 1 gang 13A Double Pole Fused Spur and Neon and Cable Outlet Black/Black | | |
| | | |
| Item Image | Wiring | Dimensions |
| | Neutral Earth Live | ELECTION VICTORIAN SPC Switched Spur & Neon & Cable Outlet |
| Primary Range | Cheriton | |
| Insert Type | 1 gang 13A Double Pole Fused Spur + Neon + Cable Outlet | |
| Plate Finish | Cheriton Victorian Box Satin Chrome | |
| Insert Colour | Black/Black | |
| EAN13 Barcode | 5017503411931 | |
| Dimensions (Nominal) | Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm | |
| Fixing Hole Centres | Box Fixing = 60.3mm Grid Fixing = N/A | |
| Minimum Wall Box Depth | 35mm | |
| Switched Poles | Double | |
| | 13 Amp | |
| Current Rating | 220/250V AC | |
| Voltage Maximum Load | 13 Amp | |
| | 50Hz | |
| Mains Frequency IP Rating | IP2XD | |
| Contact Gap Minimum | 3mm | |
| Terminal Capacity 1 | 3 x 2.5mm2 | |
| | 2 x 4mm2 Multi Strand | |
| Terminal Capacity 2 | 1 x 6mm2 | |
| Terminal Capacity 3 | | |
| Earth Terminal Capacity 1 | 6 x 1mm2 | |
| Earth Terminal Capacity 2 | 5 x 1.5mm2 | |
| Earth Terminal Capacity 3 | 3 x 2.5mm2 | |
| Earth Terminal Capacity 4 | 2 x 4mm2 Multi-strand | |
| Earth Terminal Capacity 5 | 1 x 6mm2 | |
| Product Class 1 | Must be earthed | |
| Ambient Operating Temperature | -5° to +40°C | |
| Recommended Location | Internal Use Only | |
| Maximum Installation Altitude | 2000m | |
| Cable Outlet Minimum/Maximum | Min = 0.75mm ² Max = 2.5mm ² | |
| Standard/Approval | BS 1363-4 | |
| Additional Notes | Cable Outlets Fitted with Clamps:Yes | |
| Patents and Trademarks | Cheriton is a Registered Trade Mark No. 2344779 | |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System. | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. | Correct as at 12 October 2018 04:45 PM E&OE |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Of E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in | ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84 | Listed in Trimble. LUCKINS relator 015.5Plus (Etc. No. 141128 |