




## 96US5W

### Cheriton Victorian Satin Chrome 1 gang 5A Unswitched Socket White

| Item Image  | Wiring   | Dimensions  |
|---|--|---|
|    |  <p> <span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> Neutral<br/> <span style="display: inline-block; width: 10px; height: 10px; border: 1px solid black; margin-right: 5px;"></span> Earth<br/> <span style="display: inline-block; width: 10px; height: 10px; background-color: white; border: 1px solid black; margin-right: 5px;"></span> Live         </p> |  <p> <b>Hamilton®</b><br/>           CHERITON VICTORIAN<br/>           US5<br/>           Unswitched Socket         </p> |
| Primary Range   | Cheriton   |   |
| Insert Type   | 1 gang 5A Unswitched Socket  |   |
| Plate Finish  | Cheriton Victorian Box Satin Chrome  |   |
| Insert Colour   | White  |   |
| EAN13 Barcode   | 5017503410057  |   |
| Dimensions (Nominal)  | Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm   |   |
| Weight  | 134 GR   |   |
| Fixing Hole Centres   | Box Fixing = 60.3mm Grid Fixing = N/A  |   |
| Minimum Wall Box Depth  | 35mm   |   |
| Switched Poles  | None   |   |
| Current Rating  | 5 Amp  |   |
| Voltage   | 220/250V AC  |   |
| Maximum Load  | 5 Amp  |   |
| Mains Frequency   | 50Hz   |   |
| IP Rating   | IP2XD  |   |
| Contact Gap Minimum   | None   |   |
| Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Terminal Capacity 3   | 2 x 2.5mm <sup>2</sup>   |   |
| Terminal Capacity 4   | 1 x 4mm <sup>2</sup>   |   |
| Earth Terminal Capacity 1   | 5 x 1mm <sup>2</sup>   |   |
| Earth Terminal Capacity 2   | 4 x 1.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 3   | 2 x 2.5mm <sup>2</sup>   |   |
| Earth Terminal Capacity 4   | 1 x 4mm <sup>2</sup>   |   |
| Product Class 1   | Must be earthed  |   |
| Ambient Operating Temperature   | -5° to +40°C   |   |
| Recommended Location  | Internal Use Only  |   |
| Maximum Installation Altitude   | 2000m  |   |
| Standard/Approval   | BS 546   |   |
| Additional Notes  | Shuttered: Yes   |   |
| Patents and Trademarks  | Cheriton is a Registered Trade Mark No. 2344779  |   |
| All products listed conform to current British or European standard and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.                             |
| Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.                | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.  | Correct as at 12 October 2018 04:45 PM E&OE   |