



## 984XLEDITB100

### Cheriton Victorian Black Nickel 4g 100W LED 2 Way Push On/Off Rotary Dimmer Black Nickel

| Item Image   | Wiring   | Dimensions   |
|--|--|--|
|   |  |   |
| Primary Range  | Cheriton   |  |
| Insert Type  | 4 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer                                      |  |
| Plate Finish   | Cheriton Victorian Box Black Nickel  |  |
| Insert Colour  | Black Nickel   |  |
| EAN13 Barcode  | 5017504081997  |  |
| Dimensions (Nominal)   | Double: Height = 86.5mm Width = 146.0mm Depth = 7.5mm  |  |
| Fixing Hole Centres  | Box Fixing = 120.6mm Grid Fixing = N/A   |  |
| Minimum Wall Box Depth   | 35mm   |  |
| Wattage  | 5-70W Per Gang   |  |
| Switched Poles   | Single   |  |
| Current Rating   | 0.3A Per Gang  |  |
| Voltage  | 230V-240V  |  |
| Maximum Load   | 5-70W Per Gang   |  |
| Mains Frequency  | 50Hz   |  |
| IP Rating  | IP2XD  |  |
| Terminal Capacity 1  | 2X1mm <sup>2</sup>   |  |
| Terminal Capacity 2  | 2X1.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 1  | 5X1mm <sup>2</sup>   |  |
| Earth Terminal Capacity 2  | 4X1.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 3  | 3X2.5mm <sup>2</sup>   |  |
| Earth Terminal Capacity 4  | 1X4mm <sup>2</sup> Multi-Strand  |  |
| Earth Terminal Capacity 5  | 1X6mm <sup>2</sup>   |  |
| Product Class 1  | Face plate must be earthed   |  |
| Ambient Operating Temperature  | -5°C to +40°C  |  |
| Recommended Location   | Internal Use Only  |  |
| Maximum Installation Altitude  | 2000m  |  |
| Standard/Approval  | BS EN 60669-2-1  |  |
| Additional Notes   | Trailing Edge & Leading Edge Dimmer  |  |
| Patents and Trademarks   | Cheriton is a Registered Trade Mark No. 2344779  |  |
| <p>All products listed conform to current British or European standard and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.</p>         | <p>It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.</p>                | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.</p> | <p>Correct as at 12 October 2018 04:45 PM E&amp;OE</p>   |

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ  
 T: +44 (0)1747 860088 F: +44 (0)1179 710414  
 E: info@hamilton-litestat.com www.hamilton-litestat.com

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB  
 Registered in London No. 941624 VAT Registration No. 222 6607 84

