## Hamilton

## making connections beautifully

	Wiring Accessories • Circuit Protection • Sm	nart Lighting Control & Multi-room Audio
<u>98COB</u>		
Item Image	Wiring	Dimensions
		Uppeilter
•	Prepare cord as shown below	Bas Control Co
Primary Range	Cheriton	
Insert Type	1 gang 20A Cable Outlet	
Plate Finish	Cheriton Victorian Box Black Nickel	
Insert Colour	Black	
EAN13 Barcode	5017503981762	
	Single: Height = 88.5mm Width = 88.5mm Depth = 7.5mm	
Dimensions (Nominal)	Box Fixing = $60.3$ mm Grid Fixing = N/A	
Fixing Hole Centres		
Minimum Wall Box Depth	35mm	
Switched Poles	None	
Current Rating	20 Amp	
Voltage	220/250V AC	
Maximum Load	20 Amp	
Mains Frequency	50Hz	
IP Rating	IP2XD	
Contact Gap Minimum	None	
Terminal Capacity 1	5 x 1mm2	
Terminal Capacity 2	4 x 1.5mm2	
Terminal Capacity 3	2 x 2.5mm2	
Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 1	6 x 1mm2	
Earth Terminal Capacity 2	5 x 1.5mm2	
Earth Terminal Capacity 3	3 x 2.5mm2	
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand	
Earth Terminal Capacity 5	1 x 6mm2	
Product Class 1	Must be earthed	
Ambient Operating Temperature	-5° to +40°C	
Recommended Location	Internal Use Only	
Maximum Installation Altitude	2000m	
Cable Outlet Minimum/Maximum	Min = 0.75mm <sup>2</sup> Max = 2.5mm <sup>2</sup>	
Standard/Approval	BS 5733	
Patents and Trademarks	Cheriton is a Registered Trade Mark No. 2344779	
All products listed conform to current British or European standard and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.	It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes.	Correct as at 12 October 2018 04:45 PM E&OE
R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Ro T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered O E: info@hamilton-litestat.com www.hamilton-litestat.com Registered in	ad, Brislington, Bristol, BS4 5NZ fice 1 Rushmills, Bedford Road, Northampton NN4 7YB London No. 941624 VAT Registration No. 222 6607 84	Listed in Minimuk LUCKINS Product DISSPlus US Bon Selector DISSPlus US

SL