Hamilto

making connections beautifully

ted Dome

Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio **BCDFT24AB-W** Bloomsbury Chamfered Dark Oak 4 gang 20AX 2 Way Toggle Antique Brass Fluted Dome/White Collar Item Image Wiring Dimensions Hamilton Bloomsbury T24 2 Way Toggle 163.0 Primary Range Bloomsbury Fluted Dome Insert Type 4 gang 20AX 2 Way Toggle Plate Finish Bloomsbury Chamfered Dark Oak Insert Colour Antique Brass/White Collar EAN13 Barcode 5028690022886 Dimensions (Nominal) Quad: Height = 163mm Width = 163mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm Fixing Hole Centres Box Fixing = 120.6mm x 2 Grid Fixing = N/A Minimum Wall Box Depth 25mm Switched Poles Single 20AX Current Rating 220/250V AC Voltage 20 Amp inductive Maximum Load Mains Frequency 50Hz IP Rating IP2XD Contact Gap Minimum 3mm **Terminal Capacity 1** 5 x 1mm2 **Terminal Capacity 2** 4 x 1.5mm2 **Terminal Capacity 3** 2 x 2.5mm2 **Terminal Capacity 4** 2 x 4mm2 Multi-strand **Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 2 x 4mm2 Multi-strand Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed Ambient Operating Temperature -5° to +40°C Internal Use Only **Recommended Location**



LUCKINS

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84 T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com E info

SL