## Hamilton

## making connections beautifully

|   | Wiring Accessories • Circuit Protection • Sn  | nart Lighting Control & Multi-room Audio   |
|---|---|--|
| BCLFT23AB-B   |   |  |
|   |   |  |
| Bloomsbury Chamfered Light Oak 3 gang 20AX 2 Way Toggle Antique Brass Fluted Dome/Black Collar  |   |  |
| Item Image  | Wiring  | Dimensions   |
|   | Image: space of the space o |  |
| Primary Range   | Bloomsbury Fluted Dome  |  |
| Insert Type   | 3 gang 20AX 2 Way Toggle  |  |
| Plate Finish  | Bloomsbury Chamfered Light Oak  |  |
| Insert Colour   | Antique Brass/Black Collar  |  |
| EAN13 Barcode   | 5028690001874   |  |
| Dimensions (Nominal)  | Triple: Height = 230mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm   |  |
| Fixing Hole Centres   | Box Fixing = 182mm Grid Fixing = N/A  |  |
| Minimum Wall Box Depth  | 35mm  |  |
| Switched Poles  | Single  |  |
| Current Rating  | 20AX  |  |
| Voltage   | 220/250V AC   |  |
| Maximum Load  | 20 Amp inductive  |  |
| Mains Frequency   | 50Hz  |  |
| IP Rating   | IP2XD   |  |
| Contact Gap Minimum   | 3mm   |  |
| Terminal Capacity 1   | 5 x 1mm2  |  |
| Terminal Capacity 2   | 4 x 1.5mm2  |  |
| Terminal Capacity 3   | 2 x 2.5mm2  |  |
| Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Terminal Capacity 5   | 1 x 6mm2  |  |
| Earth Terminal Capacity 1   | 6 x 1mm2  |  |
| Earth Terminal Capacity 2   | 5 x 1.5mm2  |  |
| Earth Terminal Capacity 3   | 3 x 2.5mm2  |  |
| Earth Terminal Capacity 4   | 2 x 4mm2 Multi-strand   |  |
| Earth Terminal Capacity 5   | 1 x 6mm2  |  |
| Product Class 1   | Must be earthed   |  |
| Ambient Operating Temperature   | -5° to +40°C  |  |
| Recommended Location  | Internal Use Only   |  |
| Maximum Installation Altitude   | 2000m   |  |
| Standard/Approval   | BS EN 60669-1   | F  |
| All products listed conform to current British or<br>European standard and the product information is<br>correct at the time of going to press. | All accessories are manufactured under an accredited<br>BS EN ISO 9001 : 2015 Quality Management System.  | It is the policy of the company to improve products<br>as part of our development programme.<br>Therefore, we reserve the right to alter designs<br>and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within<br>the limitations of reproduction and printing<br>process and are not binding.                | Due to manufacturing processes we cannot<br>guarantee an exact colour match and shadings of<br>of certain finishes.   | Correct as at 12 October 2018 04:28 PM<br>E&OE   |
| R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Roa<br>T: +44 (0)1747 860088 F: +44 (0)1179 710414 Registered Off            | ad, Brislington, Bristol, BS4 5NZ<br>ice 1 Rushmills, Bedford Road, Northampton NN4 7YB   | Listed in STrimble<br>Product Selector   |

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com FS DOIMINE ROAD, DISINIPUID, DISIO, DS4 3NZ Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

SL