SL

## making connections beautifully


Wiring Accessories • Circuit Protection • Smart Lighting Control & Multi-room Audio

## **BCLFT32AB-W**

Bloomsbury Chamfered Light Oak 2 gang 20AX Intermediate Toggle Antique Brass Fluted Dome/White Collar


Item Image





Intermediate switching

## Dimensions



Primary Range	Bloomsbury Fluted Dome
Insert Type	2 gang 20AX Intermediate Toggle
Plate Finish	Bloomsbury Chamfered Light Oak
Insert Colour	Antique Brass/White Collar
EAN13 Barcode	5028690002925
Dimensions (Nominal)	Double: Height = 154.0mm Width = 88.0mm Depth = 14.5mm Plinth, Collar and Dome Depth = 45.0mm
Fixing Hole Centres	Box Fixing = 120.6mm Grid Fixing = N/A
Minimum Wall Box Depth	25mm
Switched Poles	Single
Current Rating	20AX
Voltage	220/250V AC
Maximum Load	20 Amp inductive
Mains Frequency	50Hz
IP Rating	IP2XD
Contact Gap Minimum	3mm
Terminal Capacity 1	5 x 1mm2
Terminal Capacity 2	4 x 1.5mm2
Terminal Capacity 3	2 x 2.5mm2
Terminal Capacity 4	2 x 4mm2 Multi-strand
Terminal Capacity 5	1 x 6mm2
Earth Terminal Capacity 1	6 x 1mm2
Earth Terminal Capacity 2	5 x 1.5mm2
Earth Terminal Capacity 3	3 x 2.5mm2
Earth Terminal Capacity 4	2 x 4mm2 Multi-strand
Earth Terminal Capacity 5	1 x 6mm2
Product Class 1	Must be earthed
Ambient Operating Temperature	-5° to +40°C
Recommended Location	Internal Use Only

All accessories are manufactured under an accredited BS EN ISO 9001 : 2015 Quality Management System.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of

of certain finishes.

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088 F: +44 (0)1179 710414 E: info@hamilton-litestat.com www.hamilton-litestat.com

All products listed conform to current British or

European standard and the product information is

correct at the time of going to press.

Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding.

Maximum Installation Altitude

Standard/Approval

Registered Office 1 Rushmills, Bedford Road, Northampton NN4 7YB Registered in London No. 941624 VAT Registration No. 222 6607 84

2000m

BS EN 60669-1









It is the policy of the company to improve products

as part of our development programme.

Therefore, we reserve the right to alter designs

and dimensions without prior notice.



Correct as at 12 October 2018 04:29 PM

